Section	Specification	RZR® 570 In-Mold White Lightning	RZR® 570 EPS	RZR® 900	RZR® 900 Premium	RZR® 900 Fox Edition	RZR® S 900
ENGINE	Engine Type	4-Stroke DOHC Single Cylinder	4-Stroke DOHC Single Cylinder	4-Stroke DOHC Twin Cylinder	4-Stroke DOHC Twin Cylinder	4-Stroke DOHC Twin Cylinder	4-Stroke DOHC Twin Cylinder
	Horsepower / Displacement	45 hp / 567 cc	45 hp / 567 cc	75 hp / 875 cc	75 hp / 875 cc	75 hp / 875 cc	75 hp / 875 cc
	Fuel System / Cooling	Electronic Fuel Injection / Liquid	Electronic Fuel Injection / Liquid	Electronic Fuel Injection / Liquid	Electronic Fuel Injection / Liquid	Electronic Fuel Injection / Liquid	Electronic Fuel Injection / Liquid
DRIVETRAIN	Transmission / Final Drive	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H
	Drive System	True On-Demand AWD/2WD	True On-Demand AWD/2WD	True On-Demand AWD/2WD	High Performance True On-Demand AWD/2WD	High Performance True On-Demand AWD/2WD with Turf Mode	True On-Demand AWD/2WD
	Engine Braking System	Not Equipped	Standard	Standard	Standard	Standard	Standard
SUSPENSION	Front Suspension	Dual A-Arm with Stabilizer Bar and 9" (22.9 cm) Travel	Dual A-Arm with Stabilizer Bar and 9" (22.9 cm) Travel	Dual A-Arm with Stabilizer Bar and 10" (25.4 cm) Travel	Dual A-Arm with Stabilizer Bar and 10" (25.4 cm) Travel	Dual A-Arm with Stabilizer Bar and 10" (25.4 cm) Travel	Dual A-Arm with Stabilizar Bar 12.25" (31.1 cm) Travel
	Front Shocks	ZF Sachs	ZF Sachs	ZF Sachs	ZF Sachs	FOX - 2.0 Podium X (External Reservoir Shock With 24 Adjustable Clicker Positions)	FOX 2.0 PERFORMANCE PODIUM
	Rear Suspension	Dual A-Arm with Stabilizer Bar and 9.5" (24 cm) Travel	Dual A-Arm with Stabilizer Bar and 9.5" (24 cm) Travel	Dual A-Arm with Stabilizer Bar and 10" (25.4 cm) Travel	Dual A-Arm with Stabilizer Bar and 10" (25.4 cm) Travel	Dual A-Arm with Stabilizer Bar and 10" (25.4 cm) Travel	Dual A-Arm with Stabilizer Bar and 13.2" (33.5 cm) Travel
	Rear Shocks	ZF Sachs	ZF Sachs	ZF Sachs	ZF Sachs	FOX - 2.0 Podium X (External Reservoir Shock With 24 Adjustable Clicker Positions)	FOX 2.0 PERFORMANCE PODIUM
BRAKES	Front / Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers
	Parking Brake	Park in Transmission	Park in Transmission	Park in Transmission	Park in Transmission	Park in Transmission	Park in Transmission
TIRES & WHEELS	Front Tires	25 x 8-12; Ancla	25 x 8-12; Maxxis	26 x 8-12; PXT	26 x 8-12; PXT	26 x 8-12; PXT	27 x 9-12; GBC Dirt Commander
	Rear Tires	25 x 10-12; Ancla	25 x 10-12; Maxxis	26 x 9-12; PXT	26 x 9-12; PXT	26 x 9-12; PXT	27 x 11-12; GBC Dirt Commander
	Wheels	Stamped Steel	Cast Aluminum	Stamped Steel	Cast Aluminum	Cast Aluminum	Cast Aluminum
DIMENSIONS	Wheelbase	77" (196 cm)	77" (196 cm)	79" (200.7 cm)	79" (200.7 cm)	79" (200.7 cm)	79" (200.7 cm)
	Turning Radius						
	Storage (cubic inches)						
	Dry Weight	996 lb (452 kg)	1,077 lb (489 kg)	1,150 lb (522 kg)	1,176 lb (533 kg)	1207 lb (549 kg)	1,204 lb (546 kg)
	Overall Vehicle Size (L x W x H)	107.5 x 50 x 69" (273 x 127 x 175.2 cm)	107.5 x 50 x 69" (273 x 127 x 175.2 cm)	107 x 50 x 69.5" (271.8 x 127 x 176.5 cm)	107 x 50 x 69.5" (271.8 x 127 x 176.5 cm)	107 x 50 x 69.5" (271.8 x 127 x 176.5 cm)	108 x 60 x 72" (274.3 x 152.4 x 182.9 cm)
	Ground Clearance	10.5" (26.7 cm)*	10.5" (26.7 cm)*	11" (27.9 cm)*	11" (27.9 cm)*	11" (27.9 cm)*	12.5" (31.8 cm)
	Fuel Capacity	7.25 gal (27.4 L)	7.25 gal (27.4 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)
	Bed Box Dimensions (L x W x H)	20 x 40 x 9" (51 x 102 x 23 cm)	20 x 40 x 9" (51 x 102 x 23 cm)	20.7 x 37 x 7.9" (52.5 x 94 x 20 cm)	20.7 x 37 x 7.9" (52.5 x 94 x 20 cm)	20.7 x 37 x 7.9" (52.5 x 94 x 20 cm)	20.7 x 37 x 7.9" (52.5 x 94 x 20cm)
	Rear Box Capacity	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)
	Payload Capacity	740 lb (335.6 kg)	740 lb (335.6 kg)	740 lb (335.6 kg)	740 lb (335.6 kg)	740 lb (335.6 kg)	740 lb (335.6 kg)
	Hitch Towing Rating	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)
FEATURES	Hitch / Type	Standard/1.25" Receiver	Standard/1.25" Receiver	Standard/1.25" Receiver	Standard/1.25" Receiver	Standard/1.25" Receiver	Standard/1.25" Receiver
	Cargo System	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride
	Lighting	Halogen, 50W	Halogen, 55W low/ 60W high	Halogen, 55W Low/ 60W High & Red LED Tail / Brake Lights	Halogen, 55W Low/ 60W High & Red LED Tail / Brake Lights	White LED Low/High w/ Accent Lights & Red LED Tail / Brake Lights	Halogen, 55W Low/ 60W High & Red LED Tail / Brake Lights
	Ingress / Egress	Side Nets	Side Nets	Straight 1/4 Doors	Straight 1/4 Doors	Straight 1/2 Doors	Bowed 1/4 Doors
	Seats / Seat Belts / Adjustability	Base Seats	Base Seats	Bolstered Bucket Seats with Seat Slider	Bolstered Bucket Seats with Seat Slider	Bolstered Bucket Seats with Seat Slider	Bolstered Bucket Seats with Seat Slider
	Steering	Not Equipped w/ Electronic Power Steering	Electronic Power Steering	Not Equipped w/ Electronic Power Steering	Electronic Power Steering	Electronic Power Steering	Not Equipped w/ Electronic Power Steering
	Instrumentation	Single Analog Dial with 2" LCD Rider Information Center: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seatbelt Reminder Light, Gear Indicator, DC Outlet	Single Analog Dial with 2" LCD Rider Information Center: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seatbelt Reminder Light, Gear Indicator, DC Outlet	Single Analog Dial with 2" LCD Rider Information Center: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seatbelt Reminder Light, Gear Indicator, DC Outlet	Single Analog Dial with 2" LCD Rider Information Center: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seatbelt Reminder Light, Gear Indicator, DC Outlet	"RIDE COMMAND® 7" Glove-Touch Display: Digital Instrumentation, Built-In GPS, Group ride (cell and non-cell communications), Topographic Mapping, Bluetooth & USB Smartphone Connectivity, AM/FM & Weather Radio Capable, In-Vehicle Communications Capable With Optional Sena Headsets Speedometer, Odometer, Tripmeter, Tachometer, Coolant Temperature, Volt Meter, Hour Meter, Service Indicator, Clock, Gear Indicator, Fuel Gauge, Hi-Temp Light, Seatbelt Reminder Light, Fault Code Display, DC Outlet, Ambient Temp "	Single Analog Dial with 2" LCD Rider Information Center: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seatbelt Reminder Light, Gear Indicator, DC Outlet

Section	Specification	RZR® S 900 Premium	RZR® S 1000	RZR® S4 1000	RZR® XP Turbo	RZR® XP 4 Turbo	RZR® XP 1000 EPS
ENGINE	Engine Type	4-Stroke DOHC Twin Cylinder	4-Stroke DOHC Twin Cylinder	4-Stroke DOHC Twin Cylinder	4-Stroke DOHC Twin Cylinder Turbocharged	4-Stroke DOHC Twin Cylinder Turbocharged	4-Stroke DOHC Twin Cylinder
	Horsepower / Displacement	75 hp / 875 cc	100 hp / 999 cc	100 hp / 999 cc	168 hp / 925 cc	168 hp / 925 cc	110 hp / 999 cc
	Fuel System / Cooling	Electronic Fuel Injection / Liquid	Electronic Fuel Injection / Liquid	Electronic Fuel Injection / Liquid	Electronic Fuel Injection / Liquid	Electronic Fuel Injection / Liquid	Electronic Fuel Injection / Liquid
DRIVETRAIN	Transmission / Final Drive	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H
	Drive System	High Performance True On-Demand AWD/2WD	High Performance True On-Demand AWD/2WD	High Performance True On-Demand AWD/2WD	High Performance True On-Demand AWD/2WD	High Performance On-Demand True AWD/2WD	High Performance True On-Demand AWD/2WD
	Engine Braking System	Standard	Standard	Standard	Not Equipped	Not Equipped	Not Equipped
SUSPENSION	Front Suspension	Dual A-Arm with Stabilizar Bar 12.25" (31.1 cm) Travel	Dual A-Arm with Stabilizer Bar and 12.25" (31.1 cm) Travel	Dual A-Arm with Stabilizer Bar 12.25" (31.1 cm) Travel	Dual A-Arm with Stabilizer Bar and 20" (52.8 cm) Usable Travel, 16" (40.6 cm) of Wheel Travel	Dual A-Arm with Stabilizer Bar and 20" (52.8 cm) Usable Travel, 16" (40.6 cm) of Wheel Travel	Dual A-Arm with Stabilizer Bar and 20" (52.8 cm) Usable Travel, 16" (40.6 cm) of Wheel Travel
	Front Shocks	2" Walker Evans Needle with 16-Position Adjustable Clickers	2" Walker Evans Needle with 16-Position Adjustable Clickers	FOX - 2.0 Podium X (External Reservoir Shock With 24 Adjustable Clicker Positions)	2" Walker Evans Needle with 16-Position Adjustable Clickers	2" Walker Evans Needle with 16-Position Adjustable Clickers	2" Walker Evans Needle with 16-Position Adjustable Clickers
	Rear Suspension	Dual A-Arm with Stabilizer Bar and 13.2" (33.5 cm) Travel	Dual A-Arm with Stabilizer Bar and 13.2" (33.5 cm) Travel	Dual A-Arm with Stabilizer Bar 13.2" (33.5 cm) Travel	Trailing Arm with Stabilizer Bar and 20" (50.8 cm) Usable Travel, 18" (45.72 cm) Wheel Travel	Trailing Arm with Stabilizer Bar and 20" (50.8 cm) Usable Travel, 18" (45.72 cm) Wheel Travel	Travel
	Rear Shocks	2" Walker Evans Needle with 16-Position Adjustable Clickers	2" Walker Evans Needle with 16-Position Adjustable Clickers	FOX - 2.0 Podium X (External Reservoir Shock With 24 Adjustable Clicker Positions)	2.5" Walker Evans Needle with 16-Position Adjustable Clickers	2.5" Walker Evans Needle with 16-Position Adjustable Clickers	2.5" Walker Evans Needle with 16-Position Adjustable Clickers
BRAKES	Front / Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Triple-Bore Front and Dual-Bore Rear Calipers	4-Wheel Hydraulic Disc with Triple-Bore Front and Dual-Bore Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers
	Parking Brake	Park in Transmission	Park in Transmission	Park In-Transmission	Park in Transmission	Park in Transmission	Park in Transmission
TIRES & WHEELS	Front Tires	27 x 9-12; GBC Dirt Commander	27 x 9-12; GBC Dirt Commander	27 x 9-12; GBC Dirt Commander	29 x 9-14 Maxxis Bighorn	29 x 9-14 Maxxis Bighorn	29 x 9-14; Maxxis Bighorn
	Rear Tires	27 x 11-12; GBC Dirt Commander	27 x 11-12; GBC Dirt Commander	27 x 11-12; GBC Dirt Commander	29 x 11-14 Maxxis Bighorn	29 x 11-14 Maxxis Bighorn	29 x 11-14; Maxxis Bighorn
	Wheels	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum
DIMENSIONS	Wheelbase	79" (200.7 cm)	79" (200.7 cm)	106.5" (270.5 cm)	90" (228.6 cm)	117.0" (297.2 cm)	90.0" (228.6 cm)
	Turning Radius						
	Storage (cubic inches)						
	Dry Weight	1,230 lb (558 kg)	1,255 lbs (560 kg)	1,506 lbs (670 kg)	1512 lbs (687 kg)	1721 lbs (782kg)	1,448 lbs (658 kg)
	Overall Vehicle Size (L x W x H)	108 x 60 x 72" (274.3 x 152.4 x 182.9 cm)	108 x 60 x 72" (274.3 x 152.4 x 182.9 cm)	138.1 x 60 x 71.7" (350.8 x 152.4 x 182.1 cm)	119 x 64 x 73.75" (302.2 x 162.6 x 187.3 cm)	146 x 64 x 73.75" (370.8 x 162.6 x 187.3 cm)	119 x 64 x 73.75" (302.2 x 162.6 x 187.3 cm)
	Ground Clearance	12.5" (31.8 cm)	12.5" (31.8 cm)	12.5" (31.8 cm)	14" (35.56cm)	14" (35.56cm)	14" (35.56cm)
	Fuel Capacity	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)
	Bed Box Dimensions (L x W x H)	20.7 x 37 x 7.9" (52.5 x 94 x 20cm)	20.7 x 37 x 7.9" (52.5 x 94 x 20cm)	20.7 x 37 x 7.9" (52.5 x 94 x 20cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)
	Rear Box Capacity	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)
	Payload Capacity	740 lb (335.6 kg)	740 lb (335.6 kg)	900 lb (408 kg)	740 lb (335.6 kg)	900 lb (408.2 kg)	740 lb (335.6 kg)
	Hitch Towing Rating	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	N.A.	N.A.	N.A.
FEATURES	Hitch / Type	Standard/1.25" Receiver	Standard/1.25" Receiver	Standard/1.25" Receiver	Not Equipped	Not Equipped	Not Equipped
	Cargo System	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride
	Lighting	Halogen, 55W Low/ 60W High & Red LED Tail / Brake Lights	Halogen, 55W Low/ 60W High & Red LED Tail / Brake Lights	Halogen, 55W Low/ 60W High & Red LED Tail / Brake Lights	Signature Blacked Out White LED Low/High & Red LED Tail / Brake Lights	Signature Blacked Out White LED Low/High & Red LED Tail / Brake Lights	Signature Blacked Out White LED Low/High & Red LED Tail / Brake Lights
	Ingress / Egress	Bowed 1/4 Doors	Bowed 1/4 Doors	Bowed 1/4 Doors	Bowed 1/4 Doors	Bowed 1/4 Doors	Bowed 1/4 Doors
	Seats / Seat Belts / Adjustability	Bolstered Bucket Seats with Seat Slider	Bolstered Bucket Seats with Seat Slider	Bolstered Bucket Seats with Front Seat Sliders	Bolstered Bucket Seats with Seat Slider and Height Adjustable Seat Belts	Bolstered Bucket Seats with Front Seat Sliders and Rear Height Adjustable Seat Belts	Bolstered Bucket Seats with Seat Slider and Height Adjustable Seat Belts
	Steering	Electronic Power Steering	Electronic Power Steering	Electronic Power Steering	Electronic Power Steering with Quick Turn Rack	Electronic Power Steering with Quick Turn Rack	Electronic Power Steering with Quick Turn Rack
	Instrumentation	Single Analog Dial with 2" LCD Rider Information Center: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seatbelt Reminder Light, Gear Indicator, DC Outlet	Single Analog Dial with 2" LCD Rider Information Center: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seatbelt Reminder Light, Gear Indicator, DC Outlet	Single Analog Dial with 2" LCD Rider Information Center: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seatbelt Reminder Light, Gear Indicator, DC Outlet	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/ Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/ Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/ Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet

Section	Specification	RZR® XP 4 1000 EPS	RZR® XP 1000 EPS Trails and Rock Edition	RZR® XP 1000 EPS High Lifter Edition	RZR® XP 4 1000 EPS High Lifter Edition	RZR® XP 1000 Premium	RZR® XP 4-1000 Premium
ENGINE	Engine Type	4-Stroke DOHC Twin Cylinder	4-Stroke DOHC Twin Cylinder	4-Stroke DOHC Twin Cylinder	4-Stroke DOHC Twin Cylinder	4-Stroke DOHC Twin Cylinder	4-Stroke DOHC Twin Cylinder
	Horsepower / Displacement	110 hp / 999 cc	110 hp / 999 cc	110 hp / 999 cc	110 hp / 999 cc	110 hp / 999 cc	110 hp / 999 cc
	Fuel System / Cooling	Electronic Fuel Injection / Liquid	Electronic Fuel Injection / Liquid	Electronic Fuel Injection / Liquid	Electronic Fuel Injection / Liquid	Electronic Fuel Injection / Liquid	
DRIVETRAIN	Transmission / Final Drive	Automatic PVT P/R/N/L/H	Automatic PVT P-R/N/L/H (Gated Shifter) with Reduced L Gear	Automatic PVT P/R/N/L/H with Reduced L Gear	Automatic PVT P/R/N/L/H with Reduced L Gear	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H
	Drive System	High Performance True On-Demand AWD/2WD	Xtreme Performance True On-Demand Close Ratio AWD/2WD with Enhanced Low Gear Throttle Driveability	Xtreme Performance True On-Demand Close Ratio AWD/2WD	Xtreme Performance True On-Demand Close Ratio AWD/2WD	High Performance True On-Demand AWD/2WD	High Performance True On-Demand AWD/2WD
	Engine Braking System	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped
SUSPENSION	Front Suspension	Dual A-Arm with Stabilizer Bar and 20" (52.8 cm) Usable Travel, 16" (40.6 cm) of Wheel Travel	High Clearance Lower Control Arms, Dual A-Arm, 20.5" (52.07 cm) Usable Travel and 16" (40.6 cm)	High Clearance Lower Control Arms, Dual A-Arm with Stabilizer Bar, 20.5" (52.07 cm) Usable Travel and 16" (40.6 cm) Travel	High Clearance Lower Control Arms, Dual A-Arm with Stabilizer Bar, 20.5" (52.07 cm) Usable Travel and 16" (40.6 cm) Travel	Dual A-Arm with Stabilizer Bar and 20" (52.8 cm) Usable Travel, 16" (40.6 cm) of Wheel Travel	Dual A-Arm with Stabilizer Bar and 20" (52.8 cm) Usable Travel, 16" (40.6 cm) of Wheel Travel
	Front Shocks	2" Walker Evans Needle with 16-Position Adjustable Clickers	2" Walker Evans Needle Shocks with 16-Position Adjustable Clickers	2" Walker Evans with 16-Position Adjustable Clickers	2" Walker Evans with 16-Position Adjustable Clickers	2" Walker Evans Needle with 16-Position Adjustable Clickers	2" Walker Evans Needle with 16-Position Adjustable Clickers
	Rear Suspension	Trailing Arm with Stabilizer Bar and 20" (50.8 cm) Usable Travel, 18" (45.72 cm) Wheel Travel	High Clearance Radius Rods, Trailing Arm with Stabilizer Bar, 20.5" (52.07 cm) Usable Travel and 18" (45.7 cm) Travel	High Clearance Radius Rods, Trailing Arm with Stabilizer Bar, 20.5" (52.074 cm) Usable Travel and 18" (45.7 cm) Travel	High Clearance Radius Rods, Trailing Arm with Stabilizer Bar, 20.5" (52.074 cm) Usable Travel and 18" (45.7 cm) Travel	Trailing Arm with Stabilizer Bar and 20" (50.8 cm) Usable Travel, 18" (45.72 cm) Wheel Travel	Trailing Arm with Stabilizer Bar and 20" (50.8 cm) Usable Travel, 18" (45.72 cm) Wheel Travel
	Rear Shocks	2.5" Walker Evans Needle with 16-Position Adjustable Clickers	2.5" Walker Evans Needle Shocks with 16-Position Adjustable Clickers	2.5" Walker Evans with 16-Position Adjustable Clickers	2.5" Walker Evans with 16-Position Adjustable Clickers	2.5" Walker Evans Needle with 16-Position Adjustable Clickers	2.5" Walker Evans Needle with 16-Position Adjustable Clickers
BRAKES	Front / Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers
	Parking Brake	Park in Transmission	Park in Transmission	Park in Transmission	Park in Transmission	Park in Transmission	Park in Transmission
TIRES & WHEELS	Front Tires	29 x 9-14; Maxxis Bighorn	30 X 10 -14; Pro Armor Crawler XG	29.5 x 9.5-14; High Lifter Outlaw 2	29.5 x 9.5-14; High Lifter Outlaw 2	29 x 9-14; Maxxis Bighorn	29 x 9-14; Maxxis Bighorn
	Rear Tires	29 x 11-14; Maxxis Bighorn	30 X 10 -14; Pro Armor Crawler XG	29.5 x 11-14; High Lifter Outlaw 2	29.5 x 11-14; High Lifter Outlaw 2	29 x 11-14; Maxxis Bighorn	29 x 11-14; Maxxis Bighorn
	Wheels	Cast Aluminum	Cast Aluminum Beadlock	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum
DIMENSIONS	Wheelbase	117" (297.2 cm)	90.0" (228.6 cm)	90" (228.6 cm)	117.0" (297.2 cm)	90.0" (228.6 cm)	117" (297.2 cm)
	Turning Radius						
	Storage (cubic inches)						
	Dry Weight	1,659 lbs (752.5kg)	1,573 lb (715 kg)	1,545 lbs (702 kg)	1,752 lbs (783.3 kg)	1,458 lbs (663 kg)	1669 lbs (759 kg)
	Overall Vehicle Size (L x W x H)	146 x 64 x 73.75" (370.8 x 162.6 x 187.3 cm)	120 x 64 x 74.25" (304.8 x 162.6 x 188.6 cm)	122 x 64 x 75.25" (309.9 x 162.6 x 190.5 cm)	149" x 64" x 75.25" (378.4 x 162.6 x 191.1 cm)	119 x 64 x 73.75" (302.2 x 162.6 x 187.3 cm)	146 x 64 x 73.75" (370.8 x 162.6 x 187.3 cm)
	Ground Clearance	14" (35.56cm)	14.5" (36.8 cm)	15" (38.1 cm)	15" (38.1 cm)	14" (35.56cm)	14" (35.56cm)
	Fuel Capacity	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)
	Bed Box Dimensions (L x W x H)	28 x 22 x 7" (72 x 57 x 17.8 cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)	28 x 22 x 7" (see note) (72.0 x 57.0 x 17.8 cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)
	Rear Box Capacity	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)
	Payload Capacity	900 lb (408.2 kg)	740 lb (335.6 kg)	740 lb (335.6 kg)	900 lb (408.2 kg)	740 lb (335.6 kg)	900 lb (408 kg)
	Hitch Towing Rating	N.A.	N.A.	N.A.	N.A.	N.A.	N.A.
FEATURES	Hitch / Type	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped
	Cargo System	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride
	Lighting	Signature Blacked Out White LED Low/High & Red LED Tail / Brake Lights	Signature Blacked Out White LED Low/High, Rear Red LED Tail / Brake / Accent Lights, & Front Accent Lighting	Signature Blacked Out White LED Low/High, Rear Red LED Tail / Brake / Accent Lights, & Front Accent Lighting	Signature Blacked Out White LED Low/High, Rear Red LED Tail / Brake / Accent Lights, & Front Accent Lighting	Signature Blacked Out White LED Low/High, Rear Red LED Tail / Brake / Accent Lights, & Front Accent Lighting	Signature Blacked Out White LED Low/High, Rear Red LED Tail / Brake / Accent Lights, & Front Accent Lighting
	Ingress / Egress	Bowed 1/4 Doors	Bowed 1/2 Doors	Bowed 1/2 Doors	Bowed 1/2 Doors	Bowed 1/2 Doors	Bowed 1/2 Doors
	Seats / Seat Belts / Adjustability	Bolstered Bucket Seats with Front Seat Sliders and Rear Height Adjustable Seat Belts	Bolstered Bucket Seats with Seat Slider and Click 6 Seatbelt Harnesses	Bolstered Bucket Seats with Seat Slider and Height Adjustable Seat Belts	Bolstered Bucket Seats with Front Seat Sliders and Rear Height Adjustable Seat Belts	Bolstered Bucket Seats with Seat Slider and Height Adjustable Seat Belts	Bolstered Bucket Seats with Front Seat Sliders and Height Adjustable Seat Belts
	Steering	Electronic Power Steering with Quick Turn Rack	Electronic Power Steering	Electronic Power Steering	Electronic Power Steering	Electronic Power Steering with Quick Turn Rack	Electronic Power Steering with Quick Turn Rack
	Instrumentation	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/ Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/ Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/ Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/ Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet	RIDE COMMAND® 7" Glove-Touch Display: Digital Instrumentation, Built-In GPS, Group ride (cell-based or GPS based), Topographic Mapping, Bluetooth & USB Smartphone Connectivity, AM/FM & Weather Radio, In-Vehicle Communications Capable With Optional Sena Headsets Speedometer, Odometer, Tripmeter, Tachometer, Coolant Temperature, Volt Meter, Hour Meter, Service Indicator, Clock, Gear Indicator, Fuel Gauge, Hi-Temp Light, Seatbelt Reminder Light, Fault Code Display, DC Outlet, Ambient Temp	RIDE COMMAND® 7" Glove-Touch Display: Digital Instrumentation, Built-In GPS, Group ride (cell-based or GPS based), Topographic Mapping, Bluetooth & USB Smartphone Connectivity, AM/FM & Weather Radio, In-Vehicle Communications Capable With Optional Sena Headsets Speedometer, Odometer, Tripmeter, Tachometer, Coolant Temperature, Volt Meter, Hour Meter, Service Indicator, Clock, Gear Indicator, Fuel Gauge, Hi-Temp Light, Seatbelt Reminder Light, Fault Code Display, DC Outlet, Ambient Temp

Section	Specification	RZR® XP 1000 LE	RZR® XP 4 1000 LE	RZR® RS1	RZR® Turbo S	RZR® XP 4 Turbo S	RZR® XP Turbo S Velocity
ENGINE	Engine Type	4-Stroke DOHC Twin Cylinder	4-Stroke DOHC Twin Cylinder	4-Stroke DOHC Twin Cylinder	4-Stroke DOHC Twin Cylinder Turbocharged	4-Stroke DOHC Twin Cylinder Turbocharged	4-Stroke DOHC Twin Cylinder Turbocharged
	Horsepower / Displacement	110 hp / 999 cc	110 hp / 999 cc	110 HP / 999 cc	168 HP / 925 cc	168 HP / 925 cc	168 HP / 925 cc
	Fuel System / Cooling	Electronic Fuel Injection / Liquid	Electronic Fuel Injection / Liquid	Electronic Fuel Injection / Liquid	Electronic Fuel Injection / Liquid	Electronic Fuel Injection / Liquid	Electronic Fuel Injection / Liquid
DRIVETRAIN	Transmission / Final Drive	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H
	Drive System	High Performance True On-Demand AWD/2WD	High Performance True On-Demand AWD/2WD	Isolated Xtreme Performance True On-Demand AWD/2WD	Isolated Xtreme Performance True On-Demand AWD/2WD	Isolated Xtreme Performance True On-Demand AWD/2WD	Isolated Xtreme Performance True On-Demand AWD/2WD
	Engine Braking System	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped
SUSPENSION	Front Suspension	Dual A-Arm with Stabilizer Bar and 20" (52.8 cm) Usable Travel, 16" (40.6 cm) of Wheel Travel	Dual A-Arm with Stabilizer Bar and 20" (52.8 cm) Usable Travel, 16" (40.6 cm) of Wheel Travel	Dual A-Arm with Stabilizer Bar and 21" (53.4 cm) Usable Travel, 16" (40.6 cm) of Wheel Travel	High-Clearance Dual A-Arm with Stabilizer Bar and 25 in (63.5 cm) Usable Travel, 19 in (48.2 cm) of Wheel Travel	High-Clearance Dual A-Arm with Stabilizer Bar and 25 in (63.5 cm) Usable Travel, 19 in (48.2 cm) of Wheel Travel	Dual A-Arm with Stabilizer Bar and 25 in (63.5 cm) Usable Travel, 19 in (48.2 cm) of Wheel Travel
	Front Shocks	2" Walker Evans Needle with 16-Position Adjustable Clickers	2" Walker Evans Needle with 16-Position Adjustable Clickers	2" Walker Evans Needle Shocks with 16-position adjustable clickers	FOX 2.5 Podium Internal Bypass Shocks with Live Valve (Electronically Controlled Damping)	FOX 2.5 Podium Internal Bypass Shocks with Live Valve (Electronically Controlled Damping)	Walker Evans® 2.5" Velocity Needle Shock with 16-Position Adjustable Clickers
	Rear Suspension	Trailing Arm with Stabilizer Bar and 20" (50.8 cm) Usable Travel, 18" (45.72 cm) Wheel Travel	Trailing Arm with Stabilizer Bar and 20" (50.8 cm) Usable Travel, 18" (45.72 cm) Wheel Travel	Trailing Arm with Stabilizer Bar and 21" (53.3 cm) Usable Travel, 18" (45.7 cm) of Wheel Travel	Trailing Arm & High-Clearance Radius Rods with Stabilizer Bar and 25 in (63.5 cm) Usable Travel, 21 in (53.3 cm) of Wheel Travel	Trailing Arm & High-Clearance Radius Rods with Stabilizer Bar and 25 in (63.5 cm) Usable Travel, 21 in (53.3 cm) of Wheel Travel	Trailing Arm with Stabilizer Bar and 25 in (63.5 cm) Usable Travel, 21 in (53.3 cm) of Wheel Travel
	Rear Shocks	2.5" Walker Evans Needle with 16-Position Adjustable Clickers	2.5" Walker Evans Needle with 16-Position Adjustable Clickers	2.5" Walker Evans Needle Shocks with 16-Position Adjustable Clickers	FOX 3.0 Podium Internal Bypass Shocks with Live Valve (Electronically Controlled Damping)	FOX 3.0 Podium Internal Bypass Shocks with Live Valve (Electronically Controlled Damping)	Walker Evans® 3.0" Velocity Needle Shock with 16-Position Adjustable Clickers
BRAKES	Front / Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Dual-Bore Rear Calipers	4-Wheel Hydraulic Disc with Triple-Bore Front and Dual-Bore Rear Calipers	4-Wheel Hydraulic Disc with Triple-Bore Front and Dual-Bore Rear Calipers	4-Wheel Hydraulic Disc with Triple-Bore Front and Dual-Bore Rear Calipers
	Parking Brake	Park in Transmission	Park in Transmission	Park in Transmission	Park in Transmission	Park in Transmission	Park in Transmission
TIRES & WHEELS	Front Tires	29 x 9-14; Maxxis Bighorn	29 x 9-14; Maxxis Bighorn	29 x 9-14 Maxxis Bighorn	32 x 10-15; ITP COYOTE (8-Ply Rated)	32 x 10-15; ITP COYOTE (8-Ply Rated)	32 x 10-15; ITP COYOTE (8-Ply Rated)
	Rear Tires	29 x 11-14; Maxxis Bighorn	29 x 11-14; Maxxis Bighorn	29 x 11-14 Maxxis Bighorn	32 x 10-15; ITP COYOTE (8-Ply Rated)	32 x 10-15; ITP COYOTE (8-Ply Rated)	32 x 10-15; ITP COYOTE (8-Ply Rated)
	Wheels	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum
DIMENSIONS	Wheelbase	90.0" (228.6 cm)	117" (297.2 cm)	83" (210.8 cm)	90" (228.6 cm)	117" (297.2 cm)	90" (228.6 cm)
	Turning Radius						
	Storage (cubic inches)						
	Dry Weight	1,448 lbs (658 kg)	1,659 lbs (752.5kg)	1371 lbs (623kg)	1,781 lbs (810 kg)	1990 lbs (905 kg)	1731 lbs (787 kg)
	Overall Vehicle Size (L x W x H)	119 x 64 x 73.75" (302.2 x 162.6 x 187.3 cm)	146 x 64 x 73.75" (370.8 x 162.6 x 187.3 cm)	112" x 64" x 73.75" (284.5 x 162.6 x 187.3 cm)	122" x 72" x 75" (309.9 x 182.8 x 190.5 cm)	149" x 72" x 76" (378.5 x 182.8 x 194.3 cm)	122" x 72" x 75" (309.9 x 182.8 x 190.5 cm)
	Ground Clearance	14" (35.56cm)	14" (35.56cm)	13" (33 cm)	16" (40.6 cm)	16" (40.6 cm)	16" (40.6 cm)
	Fuel Capacity	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)	9.5 gal (36.0 L)
	Bed Box Dimensions (L x W x H)	28 x 22 x 7" (72 x 57 x 17.8 cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)	20.5" x 23" x 4.1 (Front/Rear)" (52 x 58 x 10.4 / 3 cm (Front/ Rear))	28 x 22 x 7" (72 x 57 x 17.8 cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)	28 x 22 x 7" (72 x 57 x 17.8 cm)
	Rear Box Capacity	300 lb (136.1 kg)	300 lb (136.1 kg)	50 lb	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)
	Payload Capacity	740 lb (335.6 kg)	900 lb (408.2 kg)	300 lb (136.1kg)	740 lb (335.6 kg)	900 lb (408 kg)	740 lb (335.6 kg)
	Hitch Towing Rating	N.A.	N.A.	N.A.	N.A.	N.A.	N.A.
FEATURES	Hitch / Type	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped
	Cargo System	Lock & Ride	Lock & Ride	-	Lock & Ride	Lock & Ride	Lock & Ride
	Lighting	Signature Blacked Out White LED Low/High, Rear Red LED Tail / Brake / Accent Lights, & Front Accent Lighting	Signature Blacked Out White LED Low/High, Rear Red LED Tail / Brake / Accent Lights, & Front Accent Lighting	Signature Blacked Out White LED Low/High & Red LED Tail / Brake Lights	Signature Blacked Out White LED Low/High, Rear Red LED Tail / Brake / Accent Lights, & Front Accent Lighting	Signature Blacked Out White LED Low/High, Rear Red LED Tail / Brake / Accent Lights, & Front Accent Lighting	Signature Blacked Out White LED Low/High & Red LED Tail / Brake Lights
	Ingress / Egress	Bowed 1/2 Doors	Bowed 1/2 Doors	LH Door	Bowed 1/2 Doors	Bowed 1/2 Doors	Bowed 1/4 Doors
	Seats / Seat Belts / Adjustability	Bolstered Bucket Seats with Seat Slider and Height Adjustable Seat Belts	Bolstered Bucket Seats with Front Seat Sliders and Rear Height Adjustable Seat Belts	Bolstered Bucket Seat with Seat Slider and Rear Height Adjustable Seat Belt	Bolstered Bucket Seats with Seat Slider and SubZero 4-point Harness	Bolstered Bucket Seats with Seat Sliders and SubZero 4-point Harness	Bolstered Bucket Seats with Seat Slider and SubZero 4-point Harness
	Steering	Electronic Power Steering with Quick Turn Rack	Electronic Power Steering with Quick Turn Rack	Electronic Power Steering with Quick Turn Rack	High Assist Electronic Power Steering with Quick Turn Rack	High Assist Electronic Power Steering with Quick Turn Rack	High Assist Electronic Power Steering with Quick Turn Rack
	Instrumentation	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/ Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/ Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/ Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet	RIDE COMMAND® 7" Glove-Touch Display: DYNAMIX Visualizer, Digital Instrumentation, Built-In GPS, Group Ride (cell-based or GPS based) Topographic Mapping, Bluetooth & USB Smartphone Connectivity, AM/FM & Weather Radio, In-Vehicle Communications Capable With Optional Sena Headsets Speedometer, Odometer, Tripmeter, Tachometer, Coolant Temperature, Volt Meter, Hour Meter, Service Indicator, Clock, Gear Indicator, Fuel Gauge, Hi-Temp Light, Seatbelt Reminder Light, Fault Code Display, DC Outlet, Ambient Temp	RIDE COMMAND® 7" Glove-Touch Display: DYNAMIX Visualizer, Digital Instrumentation, Built-In GPS, Group Ride (cell-based or GPS based) Topographic Mapping, Bluetooth & USB Smartphone Connectivity, AM/FM & Weather Radio, In-Vehicle Communications Capable With Optional Sena Headsets Speedometer, Odometer, Tripmeter, Tachometer, Coolant Temperature, Volt Meter, Hour Meter, Service Indicator, Clock, Gear Indicator, Fuel Gauge, Hi-Temp Light, Seatbelt Reminder Light, Fault Code Display, DC Outlet, Ambient Temp	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/ Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet

Section	Specification	RZR® XP 4 Turbo S Velocity	RZR® RS1	RZR® PRO XP	RZR® PRO XP PREMIUM	RZR® PRO XP ULTIMATE
ENGINE	Engine Type	4-Stroke DOHC Twin Cylinder Turbocharged	4-Stroke DOHC Twin Cylinder Turbocharged	4-Stroke DOHC Twin Cylinder Turbocharged	4-Stroke DOHC Twin Cylinder Turbocharged	4-Stroke DOHC Twin Cylinder Turbocharged
	Horsepower / Displacement	168 HP / 925 cc	110 HP / 999 cc	181 hp / 925 cc	181 hp / 925 cc	181 hp / 925 cc
	Fuel System / Cooling	Electronic Fuel Injection / Liquid	Electronic Fuel Injection / Liquid	Electronic Fuel Injection / Liquid	Electronic Fuel Injection / Liquid	Electronic Fuel Injection / Liquid
DRIVETRAIN	Transmission / Final Drive	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H
	Drive System	Isolated Xtreme Performance True On-Demand AWD/2WD	High Performance True On-Demand AWD/2WD	Isolated Xtreme Performance True On-Demand AWD/2WD	Isolated Xtreme Performance True On-Demand AWD/2WD	Isolated Xtreme Performance True On-Demand AWD/2WD
	Engine Braking System	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped
SUSPENSION	Front Suspension	Dual A-Arm with Stabilizer Bar and 25 in (63.5 cm) Usable Travel, 19 in (48.2 cm) of Wheel Travel	Dual A-Arm with Stabilizer Bar and 21" (53.4 cm) Travel	High-Clearance Dual A-Arm with Stabilizer Bar and 20" (50.8 cm) Usable Travel, 17" (43.2 cm) Wheel Travel	High-Clearance Dual A-Arm with Stabilizer Bar and 20" (50.8 cm) Usable Travel, 17" (43.2 cm) Wheel Travel	High-Clearance Dual A-Arm with Stabilizer Bar and 20" (50.8 cm) Usable Travel, 17" (43.2 cm) Wheel Travel
	Front Shocks	Walker Evans® 2.5" Velocity Needle Shock with 16-Position Adjustable Clickers	2" Walker Evans Needle Shocks with 16-position adjustable clickers	2" Walker Evans Needle with 16-Position Adjustable Clickers	2" Walker Evans Needle with 16-Position Adjustable Clickers	FOX 2.5 Podium Shocks with Live Valve (Electronically Controlled Damping)
	Rear Suspension	Trailing Arm with Stabilizer Bar and 25 in (63.5 cm) Usable Travel, 21 in (53.3 cm) of Wheel Travel	Trailing Arm with Stabilizer Bar and 21" (53.4 cm) Travel	Trailing Arm & High-Clearance Radius Rods with Stabilizer Bar and 22" (55.9 cm) Usable Travel, 20" (50.8 cm) Wheel Travel	Trailing Arm & High-Clearance Radius Rods with Stabilizer Bar and 22" (55.9 cm) Usable Travel, 20" (50.8 cm) Wheel Travel	Trailing Arm & High-Clearance Radius Rods with Stabilizer Bar and 22" (55.9 cm) Usable Travel, 20" (50.8 cm) Wheel Travel
	Rear Shocks	Walker Evans® 3.0" Velocity Needle Shock with 16-Position Adjustable Clickers	2.5" Walker Evans Needle Shocks with 16-Position Adjustable Clickers	2.5" Walker Evans Needle with 16-Position Adjustable Clickers	2.5" Walker Evans Needle with 16-Position Adjustable Clickers	FOX 2.5 Podium Shocks with Live Valve (Electronically Controlled Damping)
BRAKES	Front / Rear Brakes	4-Wheel Hydraulic Disc with Triple-Bore Front and Dual-Bore Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Dual-Bore Rear Calipers	4-Wheel Hydraulic Disc with Triple-Bore Front and Dual-Bore Rear Calipers	4-Wheel Hydraulic Disc with Triple-Bore Front and Dual-Bore Rear Calipers	4-Wheel Hydraulic Disc with Triple-Bore Front and Dual-Bore Rear Calipers
	Parking Brake	Park in Transmission	Park in Transmission	Park in Transmission	Park in Transmission	Park in Transmission
TIRES & WHEELS	Front Tires	32 x 10-15; ITP COYOTE (8-Ply Rated)	29 x 9-14 Maxxis Bighorn	30 x 10-14 Maxxis Carnivore; (8-ply rated); Wheel Size 14x6	30 x 10-14 Maxxis Carnivore; (8-ply rated); Wheel Size 14x6	30 x 10-14 Maxxis Carnivore; (8-ply rated); Wheel Size 14x6
	Rear Tires	32 x 10-15; ITP COYOTE (8-Ply Rated)	29 x 11-14 Maxxis Bighorn	30 x 10-14 Maxxis Carnivore; (8-ply rated); Wheel Size 14x7	30 x 10-14 Maxxis Carnivore; (8-ply rated); Wheel Size 14x7	30 x 10-14 Maxxis Carnivore; (8-ply rated); Wheel Size 14x7
	Wheels	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum
DIMENSIONS	Wheelbase	117" (297.2 cm)	83"	96" (243.8 cm)	96" (243.8 cm)	96" (243.8 cm)
	Turning Radius			18 ft (5.5 m)	18 ft (5.5 m)	18 ft (5.5 m)
	Storage (cubic inches)			1500 cubic in (24580.6 cubic cm)	1500 cubic in (24580.6 cubic cm)	1500 cubic in (24580.6 cubic cm)
	Dry Weight	1949 lbs (886 kg)	1340 lbs (607.8kg)	1736 lbs (789.2 kg)	1749 lbs (795.1 kg)	1773 lbs (806.0 kg)
	Overall Vehicle Size (L x W x H)	149" x 72" x 76" (378.5 x 182.8 x 194.3 cm)	112" x 64" x 73.75" (284.5 x 162.6 x 187.3 cm)	126 x 64 x 71.7" (320 x 162.6 x 182.1 cm)	126 x 64 x 71.7" (320 x 162.6 x 182.1 cm)	126 x 64 x 71.7" (320 x 162.6 x 182.1 cm)
	Ground Clearance	16" (40.6 cm)	13"	14.5" (36.8 cm)	14.5" (36.8 cm)	14.5" (36.8 cm)
	Fuel Capacity	9.5 gal (36.0 L)	9.5 gal (36.0 L)	12 gal (45.4 L)	12 gal (45.4 L)	12 gal (45.4 L)
	Bed Box Dimensions (L x W x H)	28 x 22 x 7" (72 x 57 x 17.8 cm)	20.5" x 23" x 4.1 (Front/Rear)" (52 x 58 x 10.4 / 3 cm (Front/Rear))	26 x 17.7 x 11.5" (66 x 45 x 29.2 cm)	26 x 17.7 x 11.5" (66 x 45 x 29.2 cm)	26 x 17.7 x 11.5" (66 x 45 x 29.2 cm)
	Rear Box Capacity	300 lb (136.1 kg)	50 lb	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)
	Payload Capacity	900 lb (408 kg)	300 lb (136.1kg)	740 lb (335.6 kg)	740 lb (335.6 kg)	740 lb (335.6 kg)
	Hitch Towing Rating	N.A.	N.A.	N.A.	N.A.	N.A.
FEATURES	Hitch / Type	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped
	Cargo System	Lock & Ride	-	Lock & Ride	Lock & Ride	Lock & Ride
	Lighting	Signature Blacked Out White LED Low/High & Red LED Tail / Brake Lights	White LED, Low/High & Red LED Tail / Brake Lights	Signature White LED, Low/High & Red LED Tail / Brake Lights	Signature White LED, Low/High & Red LED Tail / Brake Lights; Front, Rear, and Interior Accent Lighting	Signature White LED, Low/High & Red LED Tail / Brake Lights; Front, Rear, and Interior Accent Lighting
	Ingress / Egress	Bowed 1/4 Doors	LH Door	Vented 1/2 Door	Vented 1/2 Door	Vented 1/2 Door
	Seats / Seat Belts / Adjustability	Bolstered Bucket Seats with Seat Sliders and SubZero 4-point harness	Bolstered Bucket Seat with Seat Sliders	Bolstered Bucket Seats with 4-way adjustability (including 6" front to back toolless seat slider with tilt adjustability) and Height Adjustable Seat Belts	Bolstered Bucket Seats with 4-way adjustability (including 6" front to back toolless seat slider with tilt adjustability) and Retractable Click-6 Harnesses	Bolstered Bucket Seats with 4-way adjustability (including 6" front to back toolless seat slider with tilt adjustability) and Retractable Click-6 Harnesses
	Steering	High Assist Electronic Power Steering with Quick Turn Rack	Standard	High Assist Electronic Power Steering with Quick Turn Rack; Race Inspired Steering Wheel	High Assist Electronic Power Steering with Quick Turn Rack; Race inspired Steering Wheel with Telescoping adjustment	High Assist Electronic Power Steering with Quick Turn Rack; Race inspired Steering Wheel with Telescoping adjustment; Dynamix and Ride Command Push Button Controls
	Instrumentation	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/ Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/ Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/ Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/ Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet	RIDE COMMAND® 7" Glove-Touch Display: DYNAMIX 2.0 Visualizer, Digital Instrumentation, Built-In GPS, Group ride (cell-based or GPS based), Topographic Mapping, Bluetooth & USB Smartphone Connectivity, AM/FM & Weather Radio, In-Vehicle Communications Capable With Optional Sena Headsets, Rockford Fosgate Premium Audio (Including 2 Tweeters, 2 Front Speakers, and External 400W Amp) Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/ Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet

Section	Specification	RZR® PRO XP 4	RZR® PRO XP 4 PREMIUM	RZR® PRO XP 4 ULTIMATE	RZR® PRO XP Orange Madness LE	RZR® PRO XP 4 Orange Madness LE
ENGINE	Engine Type	4-Stroke DOHC Twin Cylinder Turbocharged	4-Stroke DOHC Twin Cylinder Turbocharged	4-Stroke DOHC Twin Cylinder Turbocharged	Turbo H.O.; 4-Stroke DOHC Twin Cylinder Turbocharged	4-Stroke DOHC Twin Cylinder Turbocharged
	Horsepower / Displacement	181 hp / 925 cc	181 hp / 925 cc	181 hp / 925 cc	181 HP / 925cc	181 HP / 925 cc
	Fuel System / Cooling	Electronic Fuel Injection / Liquid	Electronic Fuel Injection / Liquid	Electronic Fuel Injection / Liquid	Electronic Fuel Injection	Electronic Fuel Injection
DRIVETRAIN	Transmission / Final Drive	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H
	Drive System	Isolated Xtreme Performance True On-Demand AWD/2WD	Isolated Xtreme Performance True On-Demand AWD/2WD	Isolated Xtreme Performance True On-Demand AWD/2WD	Isolated Xtreme Performance True On-Demand AWD/2WD	Isolated Xtreme Performance True On-Demand AWD/2WD
	Engine Braking System	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped
SUSPENSION	Front Suspension	High-Clearance Dual A-Arm with Stabilizer Bar and 20" (50.8 cm) Usable Travel, 17" (43.2 cm) Wheel Travel	High-Clearance Dual A-Arm with Stabilizer Bar and 20" (50.8 cm) Usable Travel, 17" (43.2 cm) Wheel Travel	High-Clearance Dual A-Arm with Stabilizer Bar and 20" (50.8 cm) Usable Travel, 17" (43.2 cm) Wheel Travel	High-Clearance Dual A-Arm with Stabilizer Bar and 20 in (50.8 cm) Usable Travel, 17 in (43.2 cm) Wheel Travel	High-Clearance Dual A-Arm with Stabilizer Bar and 20 in (50.8 cm) Usable Travel, 17 in (43.2 cm) Wheel Travel
	Front Shocks	2" Walker Evans Needle with 16-Position Adjustable Clickers	2" Walker Evans Needle with 16-Position Adjustable Clickers	FOX 2.5 Podium Shocks with Live Valve (Electronically Controlled Damping)	2 in Walker Evans Needle with 16-Position Adjustable Clickers	2 in Walker Evans Needle with 16-Position Adjustable Clickers
	Rear Suspension	Trailing Arm & High-Clearance Radius Rods with Stabilizer Bar and 22" (55.9 cm) Usable Travel, 20" (50.8 cm) Wheel Travel	Trailing Arm & High-Clearance Radius Rods with Stabilizer Bar and 22" (55.9 cm) Usable Travel, 20" (50.8 cm) Wheel Travel	Trailing Arm & High-Clearance Radius Rods with Stabilizer Bar and 22" (55.9 cm) Usable Travel, 20" (50.8 cm) Wheel Travel	Trailing Arm with Stabilizer Bar and 22" (55.9 cm) Usable Travel, 20" (50.8 cm) Wheel Travel	Trailing Arm & High-Clearance Radius Rods with Stabilizer Bar and 22 in (55.9 cm) Usable Travel, 20 in (50.8 cm) Wheel Travel
	Rear Shocks	2.5" Walker Evans Needle with 16-Position Adjustable Clickers	2.5" Walker Evans Needle with 16-Position Adjustable Clickers	FOX 2.5 Podium Shocks with Live Valve (Electronically Controlled Damping)	2.5 in Walker Evans Needle with 16-Position Adjustable Clickers	2.5 in Walker Evans Needle with 16-Position Adjustable Clickers
BRAKES	Front / Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore XL Front and Dual-Bore Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore XL Front and Dual-Bore Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore XL Front and Dual-Bore Rear Calipers	4-Wheel Hydraulic Disc with Triple-Bore Front and Dual-Bore Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore XL Front and Dual-Bore Rear Calipers
	Parking Brake	Park in Transmission	Park in Transmission	Park in Transmission	Park In-Transmission	Park In-Transmission
TIRES & WHEELS	Front Tires	30 x 10-14 Maxxis Carnivore II; (8-ply rated); Wheel Size 14x6	30 x 10-14 Maxxis Carnivore II; (8-ply rated); Wheel Size 14x6	30 x 10-14 Maxxis Carnivore II; (8-ply rated); Wheel Size 14x6	30 x 10-14 MAXXIS Carnivore; Wheel Size 14x6	30 x 10-14 Maxxis Carnivore II; (8-ply rated); Wheel Size 14x6
	Rear Tires	30 x 10-14 Maxxis Carnivore II; (8-ply rated); Wheel Size 14x7	30 x 10-14 Maxxis Carnivore II; (8-ply rated); Wheel Size 14x7	30 x 10-14 Maxxis Carnivore II; (8-ply rated); Wheel Size 14x7	30 x 10-14 MAXXIS Carnivore; Wheel Size 14x7	30 x 10-14 Maxxis Carnivore II; (8-ply rated); Wheel Size 14x7
	Wheels	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum
DIMENSIONS	Wheelbase	125" (317.5 cm)	125" (317.5 cm)	125" (317.5 cm)	96 in (244 cm)	125 in (317.5 cm)
	Turning Radius	21.7 ft (6.6m)	21.7 ft (6.6m)	21.7 ft (6.6m)	18 ft (5.5 m)	21.7 ft (6.6m)
	Storage (cubic inches)	1500 cubic in (24580.6 cubic cm)	1500 cubic in (24580.6 cubic cm)	1500 cubic in (24580.6 cubic cm)	1500 cubic in (24580.6 cubic cm)	1500 cubic in (24580.6 cubic cm)
	Dry Weight	1998 lbs (906.3 kg)	2026 lbs (919.0 kg)	2044 lbs (927.1kg)	1,749 lbs (795.1 kg)	2,026 lb (919.0 kg)
	Overall Vehicle Size (L x W x H)	155 x 64 x 73.6" (393.7 x 162.6 x 186.9 cm)	155 x 64 x 73.6" (393.7 x 162.6 x 186.9 cm)	155 x 64 x 73.6" (393.7 x 162.6 x 186.9 cm)	126 x 64 x 71.7 in (320 x 162.6 x 182.1 cm)	155 x 64 x 73.6 in (393.7 x 162.6 x 186.9 cm)
	Ground Clearance	14.5" (36.8 cm)	14.5" (36.8 cm)	14.5" (36.8 cm)	14.5 in (36.8 cm)	14.5 in (36.8 cm)
	Fuel Capacity	13 gal (49.2 L)	13 gal (49.2 L)	13 gal (49.2 L)	12 gal (45.4 L)	13 gal (49.2 L)
	Bed Box Dimensions (L x W x H)	26 x 17.7 x 11.5" (66 x 45 x 29.2 cm)	26 x 17.7 x 11.5" (66 x 45 x 29.2 cm)	26 x 17.7 x 11.5" (66 x 45 x 29.2 cm)	26 x 17.7 x 11.5 in (66 x 45 x 29.2 cm)	26 x 17.7 x 11.5 in (66 x 45 x 29.2 cm)
	Rear Box Capacity	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)	300 lb (136.1 kg)
	Payload Capacity	900 lb (408 kg)	900 lb (408 kg)	900 lb (408 kg)	740 lb (336 kg)	900 lb (408.2 kg)
	Hitch Towing Rating	N.A.	N.A.	N.A.	N.A.	N.A.
FEATURES	Hitch / Type	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped
	Cargo System	Lock & Ride	Convertible Fold Flat rear seat storage with integrated tie downs points, 27.7 x 52.8 x 19.5" (70.4 x 134.1 x 49.53 cm)	Convertible Fold Flat rear seat storage with integrated tie downs points, 27.7 x 52.8 x 19.5" (70.4 x 134.1 x 49.53 cm)	Lock & Ride®	Fold Flat Rear Storage, convertible rear seat storage with integrated tie down points, 27.7 x 52.8 x 19.5 in (70.4 x 134.1 x 49.53 cm)
	Lighting	Signature White LED, Low/High & Red LED Tail / Brake Lights	Signature White LED, Low/High & Red LED Tail / Brake Lights; Front, Rear, and Interior Accent Lighting	Signature White LED, Low/High & Red LED Tail / Brake Lights; Front, Rear, and Interior Accent Lighting	Signature White LED, Low/ High & Red LED Tail / Brake Lights; Front, Rear, and Interior Accent Lighting	Signature White LED, Low/ High & Red LED Tail / Brake Lights; Front, Rear, and Interior Accent Lighting
	Ingress / Egress	Front and Rear 1/2 Door	Front and Rear 1/2 Door	Front and Rear 1/2 Door	Front and Rear 1/2 Door	Front and Rear 1/2 Door
	Seats / Seat Belts / Adjustability	Front Bolstered Bucket Seats with 4-way adjustability (including 6" front to back toolless seat sliders with tilt adjustability) and 3-point Seat Belts, Rear Stadium Style Seating with Height Adjustable Seat Belts	Front Bolstered Bucket Seats with 4-way adjustability (including 6" front to back toolless seat sliders with tilt adjustability) and Retractable Click-6 Harnesses, Rear Stadium style seating with non-retractable 6-point harnesses	Front Bolstered Bucket Seats with 4-way adjustability (including 6" front to back toolless seat sliders with tilt adjustability) and Retractable Click-6 Harnesses, Rear Stadium style seating with non-retractable 6-point harnesses	Bolstered Bucket Seats with 4-way adjustability (including 6" front to back toolless seat slider with tilt adjustability) and Retractable Click-6 Harnesses	Front Bolstered Bucket Seats with 4-way adjustability (including 6 in front to back toolless seat sliders with tilt adjustability) and Retractable Click-6 Harnesses, Rear Stadium style seating with Click-6 harnesses
	Steering	High Assist Electronic Power Steering with Quick Turn Rack; Race Inspired Steering Wheel	High Assist Electronic Power Steering with Quick Turn Rack; Race inspired Steering Wheel with Telescoping adjustment	High Assist Electronic Power Steering with Quick Turn Rack; Race inspired Steering Wheel with Telescoping adjustment; Dynamix and Ride Command Push Button Controls	High Assist Electronic Power Steering with Quick Turn Rack; Race inspired Steering Wheel with Telescoping adjustment	High Assist Electronic Power Steering with Quick Turn Rack; Race inspired Steering Wheel with Telescoping adjustment
	Instrumentation	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/ Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, Front and Rear DC Outlet	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/ Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, Front and Rear DC Outlet	RIDE COMMAND® 7" Glove-Touch Display: DYNAMIX 2.0 Visualizer, Digital Instrumentation, Built-In GPS, Group ride (cell-based or GPS based), Topographic Mapping, Bluetooth & USB Smartphone Connectivity, AM/FM & Weather Radio, In-Vehicle Communications Capable With Optional Sena Headsets, Rockford Fosgate Premium Audio (Including 2 Tweeters, 2 Front & 2 Rear Speakers, and External 400W Amp) Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/ Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, Front and Rear DC Outlet	RIDE COMMAND® 7 in Glove-Touch Display: Digital Instrumentation, Built-In GPS, Group ride (cell-based or GPS based), Topographic Mapping, Bluetooth & USB Smartphone Connectivity, AM/FM & Weather Radio, In-Vehicle Communications Capable With Optional Sena Headsets, Rockford Fosgate Premium Audio (Including 2 Tweeters, 2 Front & 2 Rear Speakers, and External 400W Amp) Dual-sweep Analog Dials w/ 4 in LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, Front and Rear DC Outlet	RIDE COMMAND® 7" Glove-Touch Display: Digital Instrumentation, Built-In GPS, Group ride (cell-based or GPS based), Topographic Mapping, Bluetooth & USB Smartphone Connectivity, AM/FM & Weather Radio, In-Vehicle Communications Capable With Optional Sena Headsets, Rockford Fosgate Premium Audio (Including 2 Tweeters, 2 Front Speakers, and External 400W Amp) Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder Light, Gear Indicator, DC Outlet