

2019 SPECIFICATIONS		ACE 500	ACE 570 EPS	ACE 900XC
ENGINE	Engine Type	ProStar SOHC 4-Stroke Twin Cylinder	ProStar DOHC 4-Stroke Single Cylinder	ProStar DOHC 4-Stroke Single Cylinder
	Horsepower / Displacement	32 HP / 500 cc	45 HP / 567 cc	78 HP / 875 cc
	Fuel System	EFI	EFI	EFI
	Cooling	Liquid	Liquid	Liquid
DRIVE TRAIN	Transmission	Automatic PVT, P/R/N/L/H	Automatic PVT, P/R/N/L/H	Automatic PVT, P/R/N/L/H
	Drive System	True On-Demand AWD/2WD	True On-Demand AWD/2WD	True On-Demand AWD/2WD
	Engine Braking System	Not Available	Not Available	Not Available
	Active Descent Control	Not Available	Not Available	Not Available
SUSPENSION	Front Suspension	MacPherson Strut, 8.2" (20.8 cm) Travel	Dual A-Arm with Stabilizer Bar, 9" (22.1 cm) Travel	Long Travel Dual A-Arm with Stabilizer Bar & Walker Evans Needle Shocks, 12.3" (31.2cm) Travel
	Rear Suspension	Dual A-Arm with Stabilizer Bar, 9.5" (24.1 cm) Travel	Dual A-Arm with Stabilizer Bar, 9.5" (24.1 cm) Travel	Long Travel Dual A-Arm with Stabilizer Bar & Walker Evans Needle Shocks, 12.6" (31.2cm) Travel
BRAKES	Front/Rear Brakes	4-Wheel Hydraulic Disc	4-Wheel Hydraulic Disc	4-Wheel Hydraulic Disc
	Parking Brake	Park In-Transmission	Park In-Transmission	Park In-Transmission
TIRES AND WHEELS	Front Tires	24" x 8" NS388	25" x 8" 489	27" x 9" Dirt Commander
	Rear Tires	24" x 10" NS388	25" x 8" 489	27" x 11" Dirt Commander
	Wheels	12" Steel	12" Steel	12" Aluminum
	Wheelbase	61.5 in (156.2 cm)	61.5 in (156.2 cm)	67.5 in (171.5 cm)
DIMENSIONS/CAPACITIES	Dry Weight	846 lb (384 kg)	900 lb (408 kg)	1,050 lb (476 kg)
	Overall Vehicle Size (L x W x H)	90 x 48 x 67.5 in (229 x 122 x 171 cm)	90 x 48 x 67.5 in (229 x 122 x 171 cm)	94 x 59 x 72 in (238 x 150 x 183 cm)
	Ground Clearance	10" (25.4 cm)	10.25" (26 cm)	13" (33cm)
	Seating Capacity	1	1	1
	Fuel Capacity	5.25 gal (19.9 L)	5.25 gal (19.9 L)	5.25 gal (19.9 L)
	Front Rack Capacity	120 lb (55 kg)	120 lb (55 kg)	120 lb (55 kg)
	Rear Rack Capacity	N/A	N/A	N/A
	Payload Capacity	575 lb (261kg)	575 lb (261kg)	575 lb (261kg)
	Hitch Towing Rating	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	Not Recommended
	Hitch/Type	Standard 1.25 in (3.2 cm) Receiver	Standard 1.25 in (3.2 cm) Receiver	None
	Cargo System	Lock & Ride, 3 Gal. (11 L) Front Dry Storage, Dual Dash Trays	Lock & Ride, 3 Gal. (11 L) Front Dry Storage, Dual Dash Trays	Lock & Ride, 3 Gal. (11 L) Front Dry Storage, Dual Dash Trays
	FEATURES	Lighting	Dual 50w Headlights	Dual 50w Headlights
Electronic Power Steering		Not Equipped	Standard	Standard
Instrumentation				
Other Standard Features		All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light, Clock, DC Outlet	All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light, Clock, DC Outlet	All Digital Gauge, Speedometer, Odometer, Tachometer, 2 Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temp, Hi-Temp Light, Clock, DC Outlet & Bluetooth Connectivity: Missed Call, Missed Text, Cell Signal Strength, Cell Battery Strength,
COLORS	Colors	Velocity Blue	Ghost Gray	Black Pearl