

2019 SPECIFICATIONS		SPORTSMAN 450 H.O.	SPORTSMAN 450 H.O. EPS	SPORTSMAN 450 H.O. UTILITY EDITION	SPORTSMAN 570	SPORTSMAN 570 EPS	SPORTSMAN 570 EPS UTILITY EDITION	SPORTSMAN 570 SP	SPORTSMAN 570 SP HUNTER EDITION	SPORTSMAN 850 HIGH LIFTER EDITION	SPORTSMAN TOURING 570	SPORTSMAN TOURING 570 EPS	SPORTSMAN TOURING 570 SP	SPORTSMAN X3 570	SPORTSMAN TOURING 850 SP	SPORTSMAN TOURING XP 1000	SPORTSMAN EX6 BIG BOSS 570 EPS		
ENGINE	Engine Type	ProStar iSOHC 4-Stroke Single Cylinder	ProStar iSOHC 4-Stroke Single Cylinder	ProStar iSOHC 4-Stroke Single Cylinder	ProStar SOHC 4-Stroke Single Cylinder	ProStar SOHC 4-Stroke Single Cylinder	ProStar SOHC 4-Stroke Single Cylinder	ProStar SOHC 4-Stroke Single Cylinder	ProStar SOHC 4-Stroke Single Cylinder	ProStar SOHC 4-Stroke Twin Cylinder	ProStar SOHC 4-Stroke Single Cylinder	ProStar SOHC 4-Stroke Single Cylinder	ProStar SOHC 4-Stroke Single Cylinder	ProStar SOHC 4-Stroke Single Cylinder	ProStar SOHC 4-Stroke Twin Cylinder	ProStar SOHC 4-Stroke Twin Cylinder	ProStar SOHC 4-Stroke Twin Cylinder		
	Horsepower / Displacement	33 HP / 900 cc	33 HP / 900 cc	33 HP / 900 cc	44 HP / 900 cc	44 HP / 900 cc	44 HP / 900 cc	44 HP / 900 cc	44 HP / 900 cc	78 HP / 900 cc	44 HP / 900 cc	44 HP / 900 cc	44 HP / 900 cc	44 HP / 900 cc	78 HP / 900 cc	88 HP / 900 cc	44 HP / 900 cc		
	Fuel System	EFI	EFI	EFI	EFI	EFI	EFI	EFI	EFI	EFI	EFI	EFI	EFI	EFI	EFI	EFI	EFI	EFI	
	Cooling	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid	
	Transmission Drive System	Automatic PVT, ProStar LH Rear On-Demand AWD	Automatic PVT, ProStar LH Rear On-Demand AWD	Automatic PVT, ProStar LH Rear On-Demand AWD	Automatic PVT, ProStar LH Rear On-Demand AWD	Automatic PVT, ProStar LH Rear On-Demand AWD	Automatic PVT, ProStar LH Rear On-Demand AWD	Automatic PVT, ProStar LH Rear On-Demand AWD	Automatic PVT, ProStar LH Rear On-Demand AWD	Automatic PVT, ProStar LH Rear On-Demand AWD	Automatic PVT, ProStar LH Rear On-Demand AWD	Automatic PVT, ProStar LH Rear On-Demand AWD	Automatic PVT, ProStar LH Rear On-Demand AWD	Automatic PVT, ProStar LH Rear On-Demand AWD	Automatic PVT, ProStar LH Rear On-Demand AWD	Automatic PVT, ProStar LH Rear On-Demand AWD	Automatic PVT, ProStar LH Rear On-Demand AWD	Automatic PVT, ProStar LH Rear On-Demand AWD	
BRAKES	Engine Braking System	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	
	Active Descent Control	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	
CHASSIS	Front Suspension	MacPherson Strut, 8.2" (20.8 cm) Travel	MacPherson Strut, 8.2" (20.8 cm) Travel	MacPherson Strut, 8.2" (20.8 cm) Travel	MacPherson Strut, 8.2" (20.8 cm) Travel	MacPherson Strut, 8.2" (20.8 cm) Travel	MacPherson Strut, 8.2" (20.8 cm) Travel	MacPherson Strut, 8.2" (20.8 cm) Travel	MacPherson Strut, 8.2" (20.8 cm) Travel	High-Clearance Arched Dual A-Arm, 7.4 in (18.8 cm) Travel	MacPherson Strut With 8.2 in (20.8 cm) Travel	MacPherson Strut With 8.2 in (20.8 cm) Travel	MacPherson Strut With 8.2 in (20.8 cm) Travel	MacPherson Strut With 8.2 in (20.8 cm) Travel	MacPherson Strut With 8.2 in (20.8 cm) Travel	MacPherson Strut With 8.2 in (20.8 cm) Travel	MacPherson Strut With 8.2 in (20.8 cm) Travel		
	Rear Suspension	Dual A-Arm, RS 9.5" (24.1 cm) Travel	Dual A-Arm, RS 9.5" (24.1 cm) Travel	Dual A-Arm, RS 9.5" (24.1 cm) Travel	Dual A-Arm, RS 9.5" (24.1 cm) Travel	Dual A-Arm, RS 9.5" (24.1 cm) Travel	Dual A-Arm, RS 9.5" (24.1 cm) Travel	Dual A-Arm, RS 9.5" (24.1 cm) Travel	Dual A-Arm, RS 9.5" (24.1 cm) Travel	Dual A-Arm, RS 9.5" (24.1 cm) Travel	Dual A-Arm, RS 9.5 in (24.1 cm) Travel	Dual A-Arm, RS 9.5 in (24.1 cm) Travel	Dual A-Arm, RS 9.5 in (24.1 cm) Travel	Dual A-Arm, RS 9.5 in (24.1 cm) Travel	Dual A-Arm, RS 9.5 in (24.1 cm) Travel	Dual A-Arm, RS 9.5 in (24.1 cm) Travel	Dual A-Arm, RS 9.5 in (24.1 cm) Travel	Dual A-Arm, RS 9.5 in (24.1 cm) Travel	
WHEELS & TIRES	Front/Rear Brakes	Single Level 3-Wheel Hydraulic Disc w/ Hydraulic Rear Foot Brake	Single Level 3-Wheel Hydraulic Disc w/ Hydraulic Rear Foot Brake	Single Level 3-Wheel Hydraulic Disc w/ Hydraulic Rear Foot Brake	Single Level 3-Wheel Hydraulic Disc w/ Hydraulic Rear Foot Brake	Single Level 3-Wheel Hydraulic Disc w/ Hydraulic Rear Foot Brake	Single Level 3-Wheel Hydraulic Disc w/ Hydraulic Rear Foot Brake	Single Level 3-Wheel Hydraulic Disc w/ Hydraulic Rear Foot Brake	Single Level 3-Wheel Hydraulic Disc w/ Hydraulic Rear Foot Brake	Single Level 3-Wheel Hydraulic Disc w/ Hydraulic Rear Foot Brake	Single Level 4-Wheel Hydraulic Disc w/ Hydraulic Rear Foot Brake	Single Level 4-Wheel Hydraulic Disc w/ Hydraulic Rear Foot Brake	Single Level 4-Wheel Hydraulic Disc w/ Hydraulic Rear Foot Brake	Single Level 4-Wheel Hydraulic Disc w/ Hydraulic Rear Foot Brake	Single Level 4-Wheel Hydraulic Disc w/ Hydraulic Rear Foot Brake	Single Level 4-Wheel Hydraulic Disc w/ Hydraulic Rear Foot Brake	Single Level 4-Wheel Hydraulic Disc w/ Hydraulic Rear Foot Brake	Single Level 4-Wheel Hydraulic Disc w/ Hydraulic Rear Foot Brake	
	Parking Brake	Park In-Transmission / Lockable Hand Lever	Park In-Transmission / Lockable Hand Lever	Park In-Transmission / Lockable Hand Lever	Park In-Transmission / Lockable Hand Lever	Park In-Transmission / Lockable Hand Lever	Park In-Transmission / Lockable Hand Lever	Park In-Transmission / Lockable Hand Lever	Park In-Transmission / Lockable Hand Lever	Park In-Transmission / Lockable Hand Lever	Park In-Transmission / Lockable Hand Lever	Park In-Transmission / Lockable Hand Lever	Park In-Transmission / Lockable Hand Lever	Park In-Transmission / Lockable Hand Lever	Park In-Transmission / Lockable Hand Lever	Park In-Transmission / Lockable Hand Lever	Park In-Transmission / Lockable Hand Lever	Park In-Transmission / Lockable Hand Lever	
DIMENSIONS	Front Tire	24" x 8" Wanda	24" x 8" Wanda	24" x 8" Wanda	24" x 8" Wanda	24" x 8" Wanda	24" x 8" Wanda	24" x 8" Wanda	24" x 8" Wanda	24" x 8" Wanda	24" x 8" Wanda	24" x 8" Wanda	24" x 8" Wanda	24" x 8" Wanda	24" x 8" Wanda	24" x 8" Wanda	24" x 8" Wanda	24" x 8" Wanda	
	Rear Tire	24" x 10" Wanda	24" x 10" Wanda	24" x 10" Wanda	24" x 10" Wanda	24" x 10" Wanda	24" x 10" Wanda	24" x 10" Wanda	24" x 10" Wanda	24" x 10" Wanda	24" x 10" Wanda	24" x 10" Wanda	24" x 10" Wanda	24" x 10" Wanda	24" x 10" Wanda	24" x 10" Wanda	24" x 10" Wanda	24" x 10" Wanda	
WEIGHTS & CAPACITIES	Wheels	12" Steel	12" Steel	12" Steel	12" Steel	12" Steel	12" Steel	12" Steel	12" Steel	14" Aluminum	12" Steel	12" Steel	12" Steel	12" Steel	14" Aluminum	12" Steel	12" Steel	12" Steel	
	Weight (w/ PTO)	66.5 in (128.8 cm)	66.5 in (128.8 cm)	66.5 in (128.8 cm)	66.5 in (128.8 cm)	66.5 in (128.8 cm)	66.5 in (128.8 cm)	66.5 in (128.8 cm)	66.5 in (128.8 cm)	66.5 in (128.8 cm)	66.5 in (128.8 cm)	66.5 in (128.8 cm)	66.5 in (128.8 cm)	66.5 in (128.8 cm)	66.5 in (128.8 cm)	66.5 in (128.8 cm)	66.5 in (128.8 cm)	66.5 in (128.8 cm)	66.5 in (128.8 cm)
CAPACITIES	Overall Width (w/ PTO)	83 x 48 x 47 in (210.8 x 121.9 x 119.4 cm)	83 x 48 x 47 in (210.8 x 121.9 x 119.4 cm)	83 x 48 x 47 in (210.8 x 121.9 x 119.4 cm)	83 x 48 x 48 in (210.8 x 121.9 x 121.9 cm)	83 x 48 x 48 in (210.8 x 121.9 x 121.9 cm)	83 x 48 x 48 in (210.8 x 121.9 x 121.9 cm)	83 x 48 x 48 in (210.8 x 121.9 x 121.9 cm)	83 x 48 x 48 in (210.8 x 121.9 x 121.9 cm)	83 x 48 x 52 in (210.8 x 121.9 x 132.0 cm)	88 x 48 x 48 in (226.4 x 121.9 x 121.9 cm)	88 x 48 x 48 in (226.4 x 121.9 x 121.9 cm)	88 x 48 x 48 in (226.4 x 121.9 x 121.9 cm)	88 x 48 x 48 in (226.4 x 121.9 x 121.9 cm)	88 x 47.8 x 58.25 in (226.7 x 120.9 x 147.9 cm)	88.5 x 47.8 x 58.25 in (226.7 x 120.9 x 147.9 cm)	88.5 x 47.8 x 58.25 in (226.7 x 120.9 x 147.9 cm)	88.5 x 47.8 x 58.25 in (226.7 x 120.9 x 147.9 cm)	
	Ground Clearance	10.5 in (26.7 cm)	10.5 in (26.7 cm)	10.5 in (26.7 cm)	11 in (27.9 cm)	11 in (27.9 cm)	11 in (27.9 cm)	11 in (27.9 cm)	11 in (27.9 cm)	11 in (27.9 cm)	13.5 in (34.3 cm)	11 in (27.9 cm)	11 in (27.9 cm)	11 in (27.9 cm)	11.25 in (28.6 cm)	11.25 in (28.6 cm)	11.25 in (28.6 cm)	11.25 in (28.6 cm)	
STORAGE	Seating Capacity	1	1	1	1	1	1	1	1	1	2	2	2	2	2	2	2	2	
	Fuel Capacity	4.5 gal (17.0 L)	4.5 gal (17.0 L)	4.5 gal (17.0 L)	4.5 gal (17.0 L)	4.5 gal (17.0 L)	4.5 gal (17.0 L)	4.5 gal (17.0 L)	4.5 gal (17.0 L)	4.5 gal (17.0 L)	6.25 gal (23.6 L)	6.25 gal (23.6 L)	6.25 gal (23.6 L)	6.25 gal (23.6 L)	6.25 gal (23.6 L)	6.25 gal (23.6 L)	6.25 gal (23.6 L)	6.25 gal (23.6 L)	
LOADING	Front Rack Capacity	80 lb (36.3 kg)	80 lb (36.3 kg)	80 lb (36.3 kg)	80 lb (36.3 kg)	80 lb (36.3 kg)	80 lb (36.3 kg)	80 lb (36.3 kg)	80 lb (36.3 kg)	N/A	80 lb (36.3 kg)	80 lb (36.3 kg)	80 lb (36.3 kg)	80 lb (36.3 kg)	80 lb (36.3 kg)	80 lb (36.3 kg)	80 lb (36.3 kg)	80 lb (36.3 kg)	
	Rear Rack Capacity	180 lb (81.6 kg)	180 lb (81.6 kg)	180 lb (81.6 kg)	180 lb (81.6 kg)	180 lb (81.6 kg)	180 lb (81.6 kg)	180 lb (81.6 kg)	180 lb (81.6 kg)	180 lb (81.6 kg)	180 lb (81.6 kg)	180 lb (81.6 kg)	180 lb (81.6 kg)	180 lb (81.6 kg)	180 lb (81.6 kg)	180 lb (81.6 kg)	180 lb (81.6 kg)	180 lb (81.6 kg)	
SAFETY	ProStar Safety Hitch Towing Rating	400 lb (181 kg)	400 lb (181 kg)	400 lb (181 kg)	400 lb (181 kg)	400 lb (181 kg)	400 lb (181 kg)	400 lb (181 kg)	400 lb (181 kg)	400 lb (181 kg)	400 lb (181 kg)	400 lb (181 kg)	400 lb (181 kg)	400 lb (181 kg)	400 lb (181 kg)	400 lb (181 kg)	400 lb (181 kg)	400 lb (181 kg)	
	Hitch/Pipe	Standard 1.25 in (3.2 cm) Receiver	Standard 1.25 in (3.2 cm) Receiver	Standard 1.25 in (3.2 cm) Receiver	Standard 1.25 in (3.2 cm) Receiver	Standard 1.25 in (3.2 cm) Receiver	Standard 1.25 in (3.2 cm) Receiver	Standard 1.25 in (3.2 cm) Receiver	Standard 1.25 in (3.2 cm) Receiver	Standard 1.25 in (3.2 cm) Receiver	Standard 1.25 in (3.2 cm) Receiver	Standard 1.25 in (3.2 cm) Receiver	Standard 1.25 in (3.2 cm) Receiver	Standard 1.25 in (3.2 cm) Receiver	Standard 1.25 in (3.2 cm) Receiver	Standard 1.25 in (3.2 cm) Receiver	Standard 1.25 in (3.2 cm) Receiver	Standard 1.25 in (3.2 cm) Receiver	
CONVENIENCE	Cargo System	Lock & Ride, 6 Gal (23 L) Front Dry Storage, 2 Gal (8 L) Rear Storage	Lock & Ride, 6 Gal (23 L) Front Dry Storage, 2 Gal (8 L) Rear Storage	Lock & Ride, 6 Gal (23 L) Front Dry Storage, 2 Gal (8 L) Rear Storage	Lock & Ride, 6 Gal (23 L) Front Dry Storage, 2 Gal (8 L) Rear Storage	Lock & Ride, 6 Gal (23 L) Front Dry Storage, 2 Gal (8 L) Rear Storage	Lock & Ride, 6 Gal (23 L) Front Dry Storage, 2 Gal (8 L) Rear Storage	Lock & Ride, 6 Gal (23 L) Front Dry Storage, 2 Gal (8 L) Rear Storage	Lock & Ride, 6 Gal (23 L) Front Dry Storage, 2 Gal (8 L) Rear Storage	Lock & Ride, 6 Gal (23 L) Front Dry Storage, 2 Gal (8 L) Rear Storage	Lock & Ride, 2 Gal (8 L) Rear Storage	Lock & Ride, 6 Gal (23 L) Front Dry Storage, 2 Gal (8 L) Rear Storage	Lock & Ride, 6 Gal (23 L) Front Dry Storage, 2 Gal (8 L) Rear Storage	Lock & Ride, 6 Gal (23 L) Front Dry Storage, 2 Gal (8 L) Rear Storage	Lock & Ride, 2 Gal (8 L) Rear Storage	Lock & Ride, 2 Gal (8 L) Rear Storage	Lock & Ride, 2 Gal (8 L) Rear Storage	Lock & Ride, 2 Gal (8 L) Rear Storage	
	Lighting	50w High Beam, Dual 50w Low Beam Headlights, Not Equipped	50w High Beam, Dual 50w Low Beam Headlights, Not Equipped	50w High Beam, Dual 50w Low Beam Headlights, Not Equipped	50w High Beam, Dual 50w Low Beam Headlights, Not Equipped	50w High Beam, Dual 50w Low Beam Headlights, Not Equipped	50w High Beam, Dual 50w Low Beam Headlights, Not Equipped	50w High Beam, Dual 50w Low Beam Headlights, Not Equipped	50w High Beam, Dual 50w Low Beam Headlights, Not Equipped	50w High Beam, Dual 50w Low Beam Headlights, Not Equipped	Dual 50w Low Beam Headlights, Not Equipped	50w High Beam, Dual 50w Low Beam Headlights, Not Equipped	50w High Beam, Dual 50w Low Beam Headlights, Not Equipped	50w High Beam, Dual 50w Low Beam Headlights, Not Equipped	50w High Beam, Dual 50w Low Beam Headlights, Not Equipped	50w High Beam, Dual 50w Low Beam Headlights, Not Equipped	50w High Beam, Dual 50w Low Beam Headlights, Not Equipped	50w High Beam, Dual 50w Low Beam Headlights, Not Equipped	50w High Beam, Dual 50w Low Beam Headlights, Not Equipped
INSTRUMENTATION	Instrumentation	All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light, Clock, DC Outlet	All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light, Clock, DC Outlet	All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light, Clock, DC Outlet	All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light, Clock, DC Outlet	All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light, Clock, DC Outlet	All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light, Clock, DC Outlet	All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light, Clock, DC Outlet	All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light, Clock, DC Outlet	All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light, Clock, DC Outlet	Analog Speedometer, Digital Odometer, Tachometer, 2 Tripmeters, Hour Meter, Clock, Service Indicator, Diagnostic Indicator, Gear Indicator, Fuel Gauge, AWD Indicator, Hi-Temp/Low-Batt Lights, DC Outlet	All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light, Clock, DC Outlet	All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light, Clock, DC Outlet	All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light, Clock, DC Outlet	All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light, Clock, DC Outlet	All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light, Clock, DC Outlet	All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light, Clock, DC Outlet	All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light, Clock, DC Outlet	All Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, AWD Indicator, Volt Meter, Coolant Temperature, Hi-Temp Light, Clock, DC Outlet
	Other Standard Features			Steel Front Bumper with Integrated 1.25" Receiver Hitch, Steel Front and Rear Racks				Steel Front Bumper with Integrated 1.25" Receiver Hitch, Steel Front and Rear Racks, Throttle On-Cruise for Precise Speed Control While Working, Rear Power Connection with Pod Mounted Control Switch		High Performance Rear On-Demand All Wheel Drive (AWD), 26" Aggressive CST Tires on 14" Cast Aluminum Wheels, Engine Braking System (EBS) with Active Descent Control (ADC), Premium Handling Dual-A-Arm Front Suspension with 8.2" of Travel, Standard Electronic Power Steering (EPS)		Factory-installed 26" 8" High-Lifter Cutaway 2 Tires, High Clearance Arched Dual A-Arm Suspension, Custom Graphics & Paint Package, Shledded Clutch & Engine Intake Ducting, High and Low Mud-Specific Transmission with Lower Gearing			Front Storage Bin	Rear View Mirrors, Front Storage Bin			
EXTERIOR	Colors	Indy Red, Sage Green	Indy Red	Ghost Gray	Polaris Pursuit Camo, Sage Green, Velocity Blue	Ghost Gray	Polaris Pursuit Camo, Sage Green, Velocity Blue	Crimson Metallic, Magnetic Gray Metallic	Polaris Pursuit Camo	Stealth Black	Indy Red	Velocity Blue	Silver Pearl	Sage Green	Silver Pearl	Crimson Metallic	Sage Green		