Section	2019 SPECIFICATIONS	RANGER EV	RANGER 500	RANGER 570	RANGER 570 EPS	RANGER CREW 570	RANGER CREW 570 EPS	RANGER 570 Full-Size
ENGINE	Engine Type	Single 48-Volt, High-Efficiency, AC-Induction Motor	4-Stroke Single Cylinder	4-Stroke Single Cylinder DOHC	4-Stroke Single Cylinder DOHC	4-Stroke Single Cylinder DOHC	4-Stroke Single Cylinder DOHC	4-Stroke Single Cylinder DOHC
	Displacement	N.A.	500cc	567cc	567cc	567cc	567cc	567cc
	Fuel System/Battery	Traditional Lead-Acid	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection
	Cooling	N.A.	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid
DRIVE TRAIN	Transmission/Final Drive	Direct Drive With Low-Noise Gears	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft
	Drive System	On-Demand True AWD/2WD/ VersaTrac Turf Mode	On-Demand True AWD/2WD/ VersaTrac Turf Mode	On-Demand True AWD/2WD/ VersaTrac Turf Mode	On-Demand True AWD/2WD/ VersaTrac Turf Mode	On-Demand True AWD/2WD/ VersaTrac Turf Mode	On-Demand True AWD/2WD/ VersaTrac Turf Mode	On-Demand True AWD/2WD/ VersaTrac Turf Mode
	Engine Braking System	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped
SUSPENSION	Front Suspension	MacPherson Strut 9" (22.9 cm) Travel	MacPherson Strut 9" (22.9 cm) Travel	MacPherson Strut 9" (22.9 cm) Travel	MacPherson Strut 9" (22.9 cm) Travel	MacPherson Strut 9" (22.9 cm) Travel	MacPherson Strut 9" (22.9 cm) Travel	MacPherson Strut 9" (22.9 cm) Travel
	Rear Suspension	Dual A-Arm, IRS 9" (22.9 cm) Travel	Dual A-Arm, IRS 10" (25.4 cm) Travel	Dual A-Arm, IRS 10" (25.4 cm) Travel	Dual A-Arm, IRS 10" (25.4 cm) Travel	Dual A-Arm, IRS 10" (25.4 cm) Travel	Dual A-Arm, IRS 10" (25.4 cm) Travel	Dual A-Arm, IRS 10.0" (25.4 cm) Travel
BRAKES	Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc	4-Wheel Hydraulic Disc	4-Wheel Hydraulic Disc	4-Wheel Hydraulic Disc with Dual-bore Front Calipers [Camo Model: 4-Wheel Hydraulic Disc with Dual-Bore Front & Rear Calipers]	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers
	Parking Brake	Hand-Actuated	Park In-Transmission	Park In-Transmission	Park In-Transmission	Park In-Transmission	Park In-Transmission	Park In-Transmission
TIRES AND WHEELS	Front Tires	25 x 9-12; Carlisle	25 x 8-12; 489	25 x 8-12; 489	25 x 8-12; 489	25 x 10-12; 489	25 x 10-12; 489	25 x 8-12; 489
	Rear Tires	25 x 9-12; Carlisle	25 x10-12 ; 489	25x10-12 ; 489	25x 10-12 ; 489	25 x 10-12; 489	25 x 10-12; 489	25 x 10-12; 489
	Wheels	Stamped Steel	Stamped Steel	Stamped Steel	Aluminum Black Xcelerator	Stamped Steel	Aluminum Black Xcelerator	Stamped Steel
DIMENSIONS/CAPACITIES	GVW (49 state)							2642 lbs
	GVW (50 State)	2762 lbs	2134 lbs	2142 lbs	2170 lbs	2648 lbs	2673 lbs	2442 lbs
	Wheelbase	72 in. (182.9 cm)	73 in. (185.4 cm)	73 in. (185.4 cm)	73 in. (185.4 cm)	105 in. (266.7 cm)	105 in. (266.7 cm)	79 in (202 cm)
	Dry Weight	1350 lbs (612 kg)	1065.92 lbs (483 kg)	1073 lbs (488 kg)	1101.92 lbs (501 kg)	1326.24 lbs (603 kg)	1351.24 lbs (614 kg)	1070.85 lb (486 kg)
	Overall Vehicle Size (L x W x H)	110 x 58 x 73 in. (279 x 147 x 185 cm)	110 x 58 x 73 in. (279 x 147 x 185 cm)	110 x 58 x 73 in. (279 x 147 x 185 cm)	110 x 58 x 73 in. (279 x 147 x 185 cm)	142 x 60 x 73 in. (361 x 152 x 185 cm)	142 x 60 x 73 in. (361 x 152 x 185 cm)	114 x 60 x 74 in. (290 x 152 x 188 cm)
	Ground Clearance	10" (25.4 cm)	10" (25.4 cm)	10" (25.4 cm)	10" (25.4 cm)	10" (25.4 cm)	10" (25.4 cm)	10.5 in. (26.7 cm)
	Seating Capacity	2	2	2	2	4	4	3
	Fuel Capacity	N.A.	9 gal (34.1 L)	9 gal (34.1 L)	9 gal (34.1 L)	9 gal (34.1 L)	9 gal (34.1 L)	9 gal (34.1 L)
	Bed Box Dimensions (L x W x H)	32 x 42 x 11.5" (81 x 107 x 29 cm)	32 x 42 x 11.5" (81 x 107 x 29 cm)	32 x 42 x 11.5" (81 x 107 x 29 cm)	32 x 42 x 11.5" (81 x 107 x 29 cm)	32 x 42 x 11.5" (81 x 107 x 29 cm)	32 x 42 x 11.5" (81 x 107 x 29 cm)	36.5 x 54 x 11.5" (93 x 137 x 29 cm)
	Front/Rear Rack Box Capacity	N.A./500 lb (226.8 kg)	N.A./500 lb (226.8 kg)	N.A./500 lb (226.8 kg)	N.A./500 lb (226.8 kg)	N.A./500 lb (226.8 kg)	N.A./500 lb (226.8 kg)	N.A./800 lb (363 kg) [CA:600 lb]
	Payload Capacity	1,000 lb (453.6 kg)	1,000 lb (453.6 kg)	1,000 lb (453.6 kg)	1,000 lb (453.6 kg)	1,250 lb (567 kg)	1,250 lb (567 kg)	1,500 lb (680.4 kg)
	Hitch Towing Rating	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1500 lb (680.4 kg)	1500 lb (680.4 kg)	1500 lb (680.4 kg)	1500 lb (680.4 kg)	1,500 lb (680.4 kg)
	Unbraked Trailer Towing Capacity	N.A.	N.A.	N.A.	N.A.	N.A.	N.A.	N.A.
	Hitch/Type	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver
FEATURES	Cargo System	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride
	Lighting	50W Headlight, LED Tail	50W Headlight, LED Tail	50W Headlight, LED Tail	50W Headlight, LED Tail	50W Headlight, LED Tail	50W Headlight, LED Tail	50W Headlight, LED Tail
	Electronic Power Steering	Not Equipped	Accessory	Accessory	Standard	Optional Accessory	Standard	Not Equipped
	Adjustable Driver's Seat	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped
	Tilt Steering	Standard	Standard	Standard	Standard	Standard	Standard	Standard
	Gauge		CPI	CPI	CPI	CPI	CPI	CPI
	Instrumentation	Digital Hour Meter, Mode Indicator, DC Outlet, Hi-Temp Light, Change Cycle Indicator, Battery Life Indicator	Single Analog Dial with 2" LCD Rider Information Center: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seatbelt Reminder Light, DC Outlet	Single Analog Dial with 2" LCD Rider Information Center: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seatbelt Reminder Light, DC Outlet	Single Analog Dial with 2" LCD Rider Information Center: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seatbelt Reminder Light, DC Outlet	Single Analog Dial with 2" LCD Rider Information Center: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seatbelt Reminder Light, DC Outlet	Single Analog Dial with 2" LCD Rider Information Center: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seatbelt Reminder Light, DC Outlet	Single Analog Dial with 2" LCD Rider Information Center: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seatbelt Reminder Light, DC Outlet
	Other Standard Features							
COLORS	Colors	Avalanche Grey , Pursuit Camo	Sage Green, Solar Red	Sage Green, Pursuit Camo	Nara Bronze	Sage Green, Pursuit Camo	Nara Bronze	Solar Red, Sage Green

Section	2019 SPECIFICATIONS	RANGER CREW 570 Full-Size	RANGER XP 900	RANGER XP 900 EPS	RANGER XP 900 EPS Premium	RANGER XP 1000 EPS	RANGER XP 1000 EPS Premium	RANGER XP 1000 EPS Premium Ride Command Package
ENGINE	Engine Type	4-Stroke Single Cylinder DOHC	4-Stroke Twin Cylinder DOHC	4-Stroke Twin Cylinder DOHC	4-Stroke Twin Cylinder DOHC	4-Stroke Twin Cylinder DOHC	4-Stroke Twin Cylinder DOHC	4-Stroke Twin Cylinder DOHC
	Displacement	567cc	875cc	875cc	875cc	999cc	999cc	999cc
	Fuel System/Battery	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection
	Cooling	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid
DRIVE TRAIN	Transmission/Final Drive	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft
	Drive System	On-Demand True AWD/2WD/ VersaTrac Turf Mode	On-Demand True AWD/2WD/ VersaTrac Turf Mode	High Performance On-Demand True AWD/2WD/ VersaTrac Turf Mode	High Performance On-Demand True AWD/2WD/ VersaTrac Turf Mode	High Performance On-Demand Ttrue AWD/2WD/ VersaTrac Turf Mode	High Performance On-Demand True AWD/2WD/ VersaTrac Turf Mode	High Performance On-Demand True AWD/2WD/ VersaTrac Turf Mode
	Engine Braking System	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Engine Braking System (EBS)	Engine Braking System (EBS)	Engine Braking System (EBS)
SUSPENSION	Front Suspension	MacPherson Strut 9" (22.9 cm) Travel	Dual A-Arm 10.0" (25.4 cm) Travel	Dual A-Arm 10.0" (25.4 cm) Travel	Dual A-Arm 10.0" (25.4 cm) Travel	Dual A-Arm 11.0" (27.94 cm) Travel	Dual A-Arm 11.0" (27.94 cm) Travel	Dual A-Arm 11.0" (27.94 cm) Travel
	Rear Suspension	Dual A-Arm, IRS 10.0" (25.4 cm) Travel	Dual A-Arm, IRS 10.0" (25.4 cm) Travel	Dual A-Arm, IRS 10.0" (25.4 cm) Travel	Dual A-Arm, IRS 10.0" (25.4 cm) Travel	Dual A-Arm, IRS 11.0" (27.94 cm) Travel	Dual A-Arm, IRS 11.0" (27.94 cm) Travel	Dual A-Arm, IRS 11.0" (27.94 cm) Travel
BRAKES	Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front & Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers
	Parking Brake	Park In-Transmission	Park In-Transmission	Park In-Transmission	Park In-Transmission	Park In-Transmission	Park In-Transmission	Park In-Transmission
TIRES AND WHEELS	Front Tires	25 x 10-12; 489	25 x 10-12; 489	25 x 10-12; 489	26 x 9-12; PXT	26 x 9-12; PXT	27 x 9-12; Maxxis MU511	27 x 9-12; Maxxis MU511
	Rear Tires	25 x 10-12; 489	25 x 11-12; 489	25 x 11-12; 489	26 x 11-12; PXT	26 x 11-12; PXT	27 x 11-12; Maxxis MU521	27 x 11-12; Maxxis MU521
	Wheels	Stamped Steel	Stamped Steel	Stamped Steel	Aluminum Black Xcelerator	Stamped Steel	Aluminum Black Xcelerator 2.0	Aluminum Black Xcelerator 2.0
DIMENSIONS/CAPACITIES	GVW (49 state)	2966 lbs	2904 lbs.	2922 lbs	2922 lbs	3,300 lb (1,496.9 kg)	3,300 lb (1,496.9 kg)	3,300 lb (1,496.9 kg)
	GVW (50 State)	2766 lbs	2504 lbs	2522 lbs	2522 lbs	CA: 3,300 lb (1,496.9 kg)	CA: 3,300 lb (1,496.9 kg)	CA: 3,300 lb (1,496.9 kg)
	Wheelbase	107 in. (272 cm)	81 in. (206 cm)	81 in. (206 cm)	81 in. (206 cm)	81 in. (206 cm)	81 in. (206 cm)	81 in. (206 cm)
	Dry Weight	1392.52 lbs. (632 kg)	1324.36 lbs (602 kg)	1342 lbs (609 kg)	1342.36 lbs (609 kg)	1,546 lb (701.25 kg) [CA: 1,556 lb]	1,565 lb (709.87 kg) [CA: 1,570 lb]	1,633 lb (740.72 kg) [CA: 1,638 lb]
	Overall Vehicle Size (L x W x H)	146 x 60 x 74 in. (370 x 152 x 188 cm)	116.5 x 60 x 76 in. (296 x 152 x 193 cm)	116.5 x 60 x 76 in. (296 x 152 x 193 cm)	116.5 x 60 x 76 in. (296 x 152 x 193 cm)	120 x 62.5 x 77 in. (305 x 158 x 196 cm)	120 x 62.5 x 77 in. (305 x 158 x 196 cm)	120 x 62.5 x 78 in. (305 x 158 x 198 cm)
	Ground Clearance	10.5 in. (26.7 cm)	11.5 in. (29.2 cm)	11.5 in. (29.2 cm)	12 in. (30.5 cm)	12.5 in. (31.75 cm)	13 in. (33 cm)	13 in. (33 cm)
	Seating Capacity	6	3	3	3	3	3	3
	Fuel Capacity	9 gal (34.1 L)	10 gal (37.9 L)	10 gal (37.9 L)	10 gal (37.9 L)	11.5 gal (43.5 L)	11.5 gal (43.5 L)	11.5 gal (43.5 L)
	Bed Box Dimensions (L x W x H)	36.5 x 54 x 11.5" (93 x 137 x 29 cm)	36.5 x 54 x 11.5 in. (93 x 137 x 29 cm)	36.5 x 54 x 11.5 in. (93 x 137 x 29 cm)	36.5 x 54 x 11.5 in. (93 x 137 x 29 cm)	36.75 x 54.25 x 12.5 in. (93.3 x 137.8 x 31.75 cm)	36.75 x 54.25 x 12.5 in. (93.3 x 137.8 x 31.75 cm)	36.75 x 54.25 x 12.5 in. (93.3 x 137.8 x 31.75 cm)
	Front/Rear Rack Box Capacity	N.A./800 lb (363 kg) [CA: 600 lb]	N.A./1,000 lb (453.6 kg) [CA:600 lbs]	N.A./1,000 lb (453.6 kg) [CA:600 lb]	N.A./1,000 lb (453.6 kg) [CA:600 lb]	N.A./1,000 lb (453.6 kg) [600 lb on CA]	N.A./1,000 lb (453.6 kg) [600 lb on CA]	N.A./1,000 lb (453.6 kg) [600 lb on CA]
	Payload Capacity	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg)	1,500 lb (680.4 kg) [1100 lb on CA Models]	1,500 lb (680.4 kg) [1100 lb on CA Models]	1,500 lb (680.4 kg) [1100 lb on CA Models]
	Hitch Towing Rating	1,500 lb (680.4 kg)	2,000 lb (907.2 kg)	2,000 lb (907.2 kg)	2,000 lb (907.2 kg)	2,500 lb (997.9 kg)	2,500 lb (1,133.9 kg)	2,500 lb (1,133.9 kg)
	Unbraked Trailer Towing Capacity	N.A.	N.A.	N.A.	N.A.	N.A.	N.A.	N.A.
	Hitch/Type	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver
FEATURES	Cargo System	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride
	Lighting	50W Headlight, LED Tail	55W low/ 60W high, LED Tail	55W low/ 60W high, LED Tail	55W low/ 60W high, LED Tail	55W low/ 60W high, LED Tail	55W low/ 60W high, LED Tail	55W low/ 60W high, LED Tail
	Electronic Power Steering	Not Equipped	Accessory Option	Standard	Standard	Standard	Standard	Standard
	Adjustable Driver's Seat	Not Equipped	Not Equipped	Not Equipped	Standard	Not Equipped	Standard	Standard
	Tilt Steering	Standard	Standard	Standard	Standard	Standard	Standard	Standard
	Gauge	CPI	CPI	CPI	CPI	B1	C4	C4
	Instrumentation	Single Analog Dial with 2" LCD Rider Information Center: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seatbelt Reminder Light, DC Outlet	Single Analog Dial with 2" LCD Rider Information Center: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seatbelt Reminder Light, DC Outlet	Single Analog Dial with 2" LCD Rider Information Center: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seatbelt Reminder Light, DC Outlet	Single Analog Dial with 2" LCD Rider Information Center: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seatbelt Reminder Light, DC Outlet	4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, Gear Indicator, DC Outlet	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet
	Other Standard Features				Premium Cut & Sew Seats	Polaris Pulse Bus Bar	Polaris Pulse Bus Bar	Display, GPS Antenna, Front/Rear Camera, 2 Audio Dash Speakers w/ AM/FM Antenna, Roof, Winch, Polaris Pulse Bus Bar
COLORS	Colors	Sage Green	Sage Green, Pursuit Camo	Sage Green, Solar Red	Military Tan, Orange Madness, Turbo Silver	Sage Green	Steel Blue, Magnetic Grey, White Pearl, PPC, Light Maroon & Sands	Steel Blue, Magnetic Grey, White Pearl, PPC

Section	2019 SPECIFICATIONS	RANGER XP 1000 EPS NorthStar Edition Ride Command Package	RANGER XP 1000 EPS NorthStar Edition	RANGER XP 1000 EPS High Lifter Edition	RANGER CREW XP 900	RANGER CREW XP 900 EPS	RANGER CREW XP 900 EPS Premium	RANGER CREW XP 1000 EPS
ENGINE	Engine Type	4-Stroke Twin Cylinder DOHC	4-Stroke Twin Cylinder DOHC	4-Stroke Twin Cylinder DOHC	4-Stroke Twin Cylinder DOHC	4-Stroke Twin Cylinder DOHC	4-Stroke Twin Cylinder DOHC	4-Stroke Twin Cylinder DOHC
	Displacement	999cc	999cc	999cc	875cc	875cc	875cc	999cc
	Fuel System/Battery	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection
	Cooling	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid
DRIVE TRAIN	Transmission/Final Drive	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft
	Drive System	High Performance On-Demand True AWD/2WD/ VersaTrac Turf Mode	High Performance On-Demand True AWD/2WD/ VersaTrac Turf Mode	High Performance On-Demand AWD/2WD	On-Demand True AWD/2WD/ VersaTrac Turf Mode	High Performance On-Demand True AWD/2WD/ VersaTrac Turf Mode	High Performance On-Demand True AWD/2WD/ VersaTrac Turf Mode	High Performance On-Demand Ttrue AWD/2WD/ VersaTrac Turf Mode
	Engine Braking System	Engine Braking System (EBS)	Engine Braking System (EBS)	Engine Braking System (EBS)	Not Equipped	Not Equipped	Not Equipped	Engine Braking System (EBS)
SUSPENSION	Front Suspension	Dual A-Arm 11.0" (27.94 cm) Travel	Dual A-Arm 11.0" (27.94 cm) Travel	Independent, Arched Lower A-arms, 11" (27.9 cm) of Travel	Dual A-Arm 10.0" (25.4 cm) Travel	Dual A-Arm 10.0" (25.4 cm) Travel	Dual A-Arm 10.0" (25.4 cm) Travel	Dual A-Arm 11.0" (27.94 cm) Travel
	Rear Suspension	Dual A-Arm, IRS 11.0" (27.94 cm) Travel	Dual A-Arm, IRS 11.0" (27.94 cm) Travel	Independent, Arched Lower A-arms, 11" (27.9 cm) of Travel	Dual A-Arm, IRS 10.0" (25.4 cm) Travel	Dual A-Arm, IRS 10.0" (25.4 cm) Travel	Dual A-Arm, IRS 10.0" (25.4 cm) Travel	Dual A-Arm, IRS 11.0" (27.94 cm) Travel
BRAKES	Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers
	Parking Brake	Park In-Transmission	Park In-Transmission	Park In-Transmission	Park In-Transmission	Park In-Transmission	Park In-Transmission	Park In-Transmission
TIRES AND WHEELS	Front Tires	27 x 9-12; Maxxis MU511	27 x 9-12; Maxxis MU511	28 x 9.5-14; Outlaw 2	26 x 9-12; PXT	26 x 9-12; PXT	26 x 9-12; PXT	26 x 9-12; PXT
	Rear Tires	27 x 11-12; Maxxis MU521	27 x 11-12; Maxxis MU521	28 x 11-14; Outlaw 2	26 x 11-12; PXT	26 x 11-12; PXT	26 x 11-12; PXT	26 x 11-12; PXT
	Wheels	Aluminum Black Xcelerator 2.0	Aluminum Black Xcelerator 2.0	Cast Aluminum Buckle	Stamped Steel	Stamped Steel	Aluminum Black Xcelerator	Stamped Steel
DIMENSIONS/CAPACITIES	GVW (49 state)	3,600 lb (1,632.9 kg)	3,600 lb (1,632.9 kg)	3340 lbs	3444 lbs	3444 lbs	3444 lbs	3,690 lb (1,673.8 kg)
	GVW (50 State)	CA: 3,600 lb (1,632.9 kg)	CA: 3,600 lb (1,632.9 kg)	NA	3044 lbs	3044 lbs	3044 lbs	3,290 lb (1,492.3 kg)
	Wheelbase	81 in. (206 cm)	81 in. (206 cm)	81 in. (2057 cm)	113 in. (287 cm)	113 in. (287 cm)	113 in. (287 cm)	113 in. (287 cm)
	Dry Weight	1,939 lb (879.52 kg) [CA: 1,944 lb]	1,875 lb (850 kg)	1773 lbs (804 kg)	1612.03 lbs (733 kg)	1629.03 lbs (738.9 kg)	1629.03 lbs (738.9 kg)	1,810 lbs (821 kg)
	Overall Vehicle Size (L x W x H)	120 x 65 x 78 in. (305 x 165 x 198 cm)	120 x 65 x 78 in. (305 x 165 x 198 cm)	122 x 65 x 78 in. (310 x 165 x 198 cm)	148.5 x 61 x 76 in. (377 x 155 x 193 cm)	148.5 x 61 x 76 in. (377 x 155 x 193 cm)	148.5 x 61 x 76 in. (377 x 155 x 193 cm)	152 x 62.5 x 77 in. (386 x 158 x 196 cm)
	Ground Clearance	13 in. (33 cm)	13 in. (33 cm)	13.5 in (34.3 cm)	11.3 in. (28.7 cm)	11.3 in. (28.7 cm)	11.3 in. (28.7 cm)	12.5 in. (31.75 cm)
	Seating Capacity	3	3	3	6	6	6	6
	Fuel Capacity	11.5 gal (43.5 L)	11.5 gal (43.5 L)	11.5 gal (43.5 L)	10 gal (37.9 L)	10 gal (37.9 L)	10 gal (37.9 L)	11.5 gal (43.5 L)
	Bed Box Dimensions (L x W x H)	36.75 x 54.25 x 12.5 in. (93.3 x 137.8 x 31.75 cm)	36.75 x 54.25 x 12.5 in. (93.3 x 137.8 x 31.75 cm)	36.75 x 54.25 x 12.5 in. (93.3 x 137.8 x 31.75 cm)	36.5 x 54 x 11.5 in. (93 x 137 x 29 cm)	36.5 x 54 x 11.5 in. (93 x 137 x 29 cm)	36.5 x 54 x 11.5 in. (93 x 137 x 29 cm)	36.75 x 54.25 x 12.5 in. (93.3 x 137.8 x 31.75 cm)
	Front/Rear Rack Box Capacity	N.A./1,000 lb (453.6 kg) [600 lb on CA]	N.A./1,000 lb (453.6 kg) [600 lb on CA]	N.A./1,000 lb (453.6 kg)	N.A./1,000 lb (453.6 kg) [CA: 600 lb]	N.A./1,000 lb (453.6 kg) [CA: 600 lb]	N.A./1,000 lb (453.6 kg) [CA: 600 lb]	N.A./1,000 lb (453.6 kg) [600 lb on CA]
	Payload Capacity	1,275 lb (578.3 kg)	1,275 lb (578.3 kg)	1,500 lb (680.4 kg)	1,750 lb (793.8 kg)	1,750 lb (793.8 kg)	1,750 lb (793.8 kg)	1,750 lb (793.8 kg)
	Hitch Towing Rating	2,500 lb (1,133.9 kg)	2,500 lb (1,133.9 kg)	2,500 lbs. (1134 kg)	2,000 lb (907.2 kg)	2,000 lb (907.2 kg)	2,000 lb (907.2 kg)	2,500 lb (1,133.9 kg)
	Unbraked Trailer Towing Capacity	N.A.	N.A.	N.A.	N.A.	N.A.	N.A.	N.A.
	Hitch/Type	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver
FEATURES	Cargo System	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride
	Lighting	55W low/ 60W high, LED Tail	55W low/ 60W high, LED Tail	55W low/ 60W high, LED Tail	55W low/ 60W high	55W low/ 60W high	55W low/ 60W high	55W low/ 60W high, LED Tail
	Electronic Power Steering	Standard	Standard	Standard	Optional Accesory	Standard	Standard	Standard
	Adjustable Driver's Seat	Standard	Standard	Standard	Not Equipped	Not Equipped	Standard	Not Equipped
	Tilt Steering	Standard	Standard	Standard	Standard	Standard	Standard	Standard
	Gauge	C4	C4	C4	CPI	CPI	CPI	B1
	Instrumentation	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet	Single Analog Dial with 2" LCD Rider Information Center: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seatbelt Reminder Light, DC Outlet	Single Analog Dial with 2" LCD Rider Information Center: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seatbelt Reminder Light, DC Outlet	Single Analog Dial with 2" LCD Rider Information Center: Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seatbelt Reminder Light, DC Outlet	4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, Gear Indicator, DC Outlet
	Other Standard Features	Premium Pro-Fit Cab, Fixed Glass Windshield with Wiper, Rear Glass Panel, Dome Light, Rearview Mirror, Heat, AC, Defrost & Cut and Sew seats,Display, GPS Antenna, Front/Rear Camera, 2 Audio Dash Speakers w/ AM/FM Antenna, Winch, Polaris Pulse Bus Bar	Premium Pro-Fit Cab, Fixed Glass Windshield with Wiper, Rear Glass Panel, Dome Light, Rearview Mirror, Heat, AC, Defrost & Cut and Sew seats, Polaris Pulse Bus Bar	1/2 Doors (Mud specific), Mirror, Mudder Specific Bumper, Rear Bumper, 4500 lb Winch, Polaris Pulse Bus Bar			Premium Cut & Sew Seats	Polaris Pulse Bus Bar
COLORS	Colors	Steel Blue, Magnetic Grey, White Pearl, PPC	Steel Blue, Magnetic Grey, White Pearl, PPC	Stealth Black	Sage Green	Polaris Pursuit Camo	Turbo Silver	Sage Green

Section	2019 SPECIFICATIONS	RANGER CREW XP 1000 EPS Polaris Pursuit Camo	RANGER CREW XP 1000 EPS Premium	RANGER CREW XP 1000 EPS High Lifter Edition	RANGER CREW XP 1000 EPS NorthStar Edition	RANGER XP 1000 EPS Back Country Edition	RANGER CREW XP 1000 EPS Back Country Edition
ENGINE	Engine Type	4-Stroke Twin Cylinder DOHC	4-Stroke Twin Cylinder DOHC	4-Stroke Twin Cylinder DOHC	4-Stroke Twin Cylinder DOHC	4-Stroke Twin Cylinder DOHC	4-Stroke Twin Cylinder DOHC
	Displacement	999cc	999cc	999cc	999cc	999cc	999cc
	Fuel System/Battery	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection
	Cooling	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid
DRIVE TRAIN	Transmission/Final Drive	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft	Automatic PVT H/L/N/R/P; Shaft
	Drive System	High Performance On-Demand Ttrue AWD/2WD/ VersaTrac Turf Mode	High Performance On-Demand Ttrue AWD/2WD/ VersaTrac Turf Mode	High Performance On-Demand AWD/2WD	High Performance On-Demand True AWD/2WD/ VersaTrac Turf Mode	High Performance On-Demand AWD/2WD	High Performance On-Demand AWD/2WD
	Engine Braking System	Engine Braking System (EBS)	Engine Braking System (EBS)	Engine Braking System (EBS)	Engine Braking System (EBS)	Engine Braking System (EBS)	Engine Braking System (EBS)
SUSPENSION	Front Suspension	Dual A-Arm 11.0" (27.94 cm) Travel	Dual A-Arm 11.0" (27.94 cm) Travel	Independent, Arched Lower A-arms, 11" (27.9 cm) of Travel	Dual A-Arm 11.0" (27.94 cm) Travel	Independent, Arched Lower A-arms, 11" (27.9 cm) of Travel	Independent, Arched Lower A-arms, 11" (27.9 cm) of Travel
	Rear Suspension	Dual A-Arm, IRS 11.0" (27.94 cm) Travel	Dual A-Arm, IRS 11.0" (27.94 cm) Travel	Independent, Arched Lower A-arms, 11" (27.9 cm) of Travel	Dual A-Arm, IRS 11.0" (27.94 cm) Travel	Independent, Arched Lower A-arms, 11" (27.9 cm) of Travel	Independent, Arched Lower A-arms, 11" (27.9 cm) of Travel
BRAKES	Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers
	Parking Brake	Park In-Transmission	Park In-Transmission	Park In-Transmission	Park In-Transmission	Park In-Transmission	Park In-Transmission
TIRES AND WHEELS	Front Tires	27 x 9-12; Maxxis MU511	27 x 9-12; Maxxis MU511	28 x 9.5-14; Outlaw 2	27 x 9-12; Maxxis MU511	27 x 9-12; Maxxis MU511	27 x 9-12; Maxxis MU511
	Rear Tires	27 x 11-12; Maxxis MU521	27 x 11-12; Maxxis MU521	28 x 11-14; Outlaw 2	27 x 11-12; Maxxis MU521	27 x 11-12; Maxxis MU521	27 x 11-12; Maxxis MU521
	Wheels	Aluminum Black Xcelerator 2.0	Aluminum Black Xcelerator 2.0	Cast Aluminum Buckle	Aluminum Black Xcelerator 2.0	Aluminum Black Xcelerator 2.0	Aluminum Black Xcelerator 2.0
DIMENSIONS/CAPACITIES	GVW (49 state)	3,690 lb (1,673.8 kg)	3,690 lb (1,673.8 kg)	3933 lbs	3,750 lb (1,700.9 kg)	3317 lbs	3750 lbs
	GVW (50 State)	3,290 lb (1,492.3 kg)	3,290 lb (1,492.3 kg)	NA	N/A		
	Wheelbase	113 in. (287 cm)	113 in. (287 cm)	113 in. (287 cm)	113 in. (287 cm)	81 in. (206 cm)	113 in. (287 cm)
	Dry Weight	1,829 lbs (830 kg)	1,829 lbs (830 kg)	2116 lbs (960 kg)	2290 lbs (1,039 kg)	1597 lbs (724.3 kg)	1864 lbs (845 kg)
	Overall Vehicle Size (L x W x H)	152 x 62.5 x 77 in. (386 x 158 x 196 cm)	152 x 62.5 x 77 in. (386 x 158 x 196 cm)	154 x 65 x 78 in. (391 x 165 x 198 cm)	152 x 65 x 78 in. (386 x 165 x 198 cm)	120 x 62.5 x 77 in. (305 x 158 x 196 cm)	152 x 62.5 x 77 in. (386 x 158 x 196 cm)
	Ground Clearance	13 in. (33 cm)	13 in. (33 cm)	13.5 in (34.3 cm)	13 in. (33 cm)	13 in. (33 cm)	13 in. (33 cm)
	Seating Capacity	6	6	6	6	3	6
	Fuel Capacity	11.5 gal (43.5 L)	11.5 gal (43.5 L)	11.5 gal (43.5 L)	11.5 gal (43.5 L)	11.5 gal (43.5 L)	11.5 gal (43.5 L)
	Bed Box Dimensions (L x W x H)	36.75 x 54.25 x 12.5 in. (93.3 x 137.8 x 31.75 cm)	36.75 x 54.25 x 12.5 in. (93.3 x 137.8 x 31.75 cm)	36.75 x 54.25 x 12.5 in. (93.3 x 137.8 x 31.75 cm)	36.75 x 54.25 x 12.5 in. (93.3 x 137.8 x 31.75 cm)	36.75 x 54.25 x 12.5 in. (93.3 x 137.8 x 31.75 cm)	36.75 x 54.25 x 12.5 in. (93.3 x 137.8 x 31.75 cm)
	Front/Rear Rack Box Capacity	N.A./1,000 lb (453.6 kg) [600 lb on CA]	N.A./1,000 lb (453.6 kg) [600 lb on CA]	N.A./1,000 lb (453.6 kg)	N.A./1,000 lb (453.6 kg) [600 lb on CA]	N.A./1,000 lb (453.6 kg) [600 lb on CA]	N.A./1,000 lb (453.6 kg)
	Payload Capacity	1,750 lb (793.8 kg)	1,750 lb (793.8 kg)	1,525 lbs. (692 kg)	1,350 lbs (612.3 kg)	1,500 lb (680.4 kg)	1,750 lb (793.8 kg)
	Hitch Towing Rating	2,500 lb (1,133.9 kg)	2,500 lb (1,133.9 kg)	2,500 lbs. (1134 kg)	2,500 lb (1,133.9 kg)	2,500 lbs. (1133.9 kg)	2,500 lbs. (1134 kg)
	Unbraked Trailer Towing Capacity	N.A.	N.A.	N.A.	N.A.	N.A.	N.A.
	Hitch/Type	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver	Standard/2" Receiver
FEATURES	Cargo System	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride
	Lighting	55W low/ 60W high, LED Tail	55W low/ 60W high, LED Tail	55W low/ 60W high, LED Tail	55W low/ 60W high, LED Tail	55W low/ 60W high, LED Tail	55W low/ 60W high, LED Tail
	Electronic Power Steering	Standard	Standard	Standard	Standard	Standard	Standard
	Adjustable Driver's Seat	Standard	Standard	Standard	Standard	Standard	Standard
	Tilt Steering	Standard	Standard	Standard	Standard	Standard	Standard
	Gauge	C4	C4	C4	C4	C4	C4
	Instrumentation	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet
	Other Standard Features	Polaris Pulse Bus Bar	Polaris Pulse Bus Bar	1/2 Doors (Mud Specific), Mirror, Mudder Specific Bumper, Rear Bumper, 4500 lb Winch, Polaris Pulse Bus Bar	Premium Pro-Shield Cab, Fixed Glass Windshield with Wiper, Rear Glass Panel, Dome Light, Rearview Mirror, Heat, A/C, Defrost and Cut & Sew seats	High Mounted Intakes, Sealed Electrical, High Clearance Arched A-Arms, 4,500 lbs Winch, 900W Stator, Polaris Pulse Bus Bar	High Mounted Intakes, Sealed Electrical, High Clearance Arched A-Arms, 4,500 lbs Winch, 900W Stator, Polaris Pulse Bus Bar
COLORS	Colors	Pursuit Camo	Sunset Red	Stealth Black	Sunset Red Metallic	Polaris Pursuit Camo	Polaris Pursuit Camo